







# **ABOUT VANGUARD**

The year was 1986. Vanguard was a brand-new camera tripod maker with a small manufacturing facility.

The company's odds for success in a crowded market were slim, but this didn't stop a determined young woman from believing



# **VANGUARD HUNTING**

#### 00 VANGUARD

| ABOUT VANGUARD    |  |
|-------------------|--|
| TABLE OF CONTENTS |  |
| FACTORY           |  |
| KEY FEATURES      |  |
| GALLERY           |  |
| NEW PRODUCTS      |  |

## OI SPOTTING SCOPES

| ENDEAVOR HD              |
|--------------------------|
| ENDEAVOR XF              |
| VEO HD                   |
| VESTA SPOTTING SCOPE KIT |

#### 02 BINOCULARS & MONOCULARS

| ENDEAVOR ED IV |   |
|----------------|---|
| ENDEAVOR ED II |   |
| ENDEAVOR ED    | 2 |
| VEO HD IV      |   |
| VEO HD2        | 2 |
| VEO HD 2 1042M |   |
| VEO HD         | 2 |
| VEO ED         |   |
| VEO ED 8420M   | 2 |

#### 02 BINOCULARS & MONOCULARS

| VEO XF               | 27  |
|----------------------|---|
| VESTA                | 28  |
| VESTA 8320M          | 29  |
| OPTICS ACCESSORIES - | 30  |
| OPTIC GUARD          | 3I  |
|                      | VEO XF  VESTA  VESTA 8320M  OPTICS ACCESSORIES  OPTIC GUARD |

#### TRIPODS

| NEW | VEO 3 AV/CV  |
|-----|--------------|
|     | VEO 3 AB/CB  |
| NEW | VEO 3 AO/CO  |
| NEW | VEO 3T/3TT   |
| NEW | VEO 3GO/3GOT |
|     | VEO 2 PRO    |
|     | VESTA TB     |
|     | VESTA        |

#### HEADS

| NEW | VEO PH-28/26 |
|-----|--------------|
| NEW | VEO PV-20/18 |
|     | VEO CP KIT   |
| NEW | VEO QS-360   |
| NEW | VEO LVL-60   |

#### 05 SHOOTING SUPPORTS

| W | ENDEAVOR GM-70     | ł |
|---|--------------------|---|
| w | ENDEAVOR 303A/CGM  | Ę |
|   | EQUALIZER          | ļ |
|   | VEO 2              | I |
|   | QUEST              |   |
|   | SCOUT              |   |
|   | VEO 2 WINDOW MOUNT |   |
|   | PH WINDOW MOUNTS   | I |
|   | PORTA-AIM          |   |
|   | ESPOD CX           |   |
|   | VESTA TTI          |   |
|   | VS-82              | E |
|   | QUICK SHOES        | _ |
|   | ENDEAVOR SLINGS    | - |
|   |                    |   |

#### 00 VANGUARD

| SPEC SHEET | 63 |
|------------|----|
|------------|----|

# **FACTORY**


Growing into a global leader since its founding in 1986, VANGUARD provides more than our competitors because we are the factory. There are no third-party factories, development or design firms, or other outsourcing of any kind in the process. More than 1,000 Vanguard employees create the products and power the brand within our robust global operation. Every step of the process is orchestrated by Vanguard's in-house R & D, production, administration, marketing, and sales teams in Vanguard-owned and controlled facilities. This enables us to ensure standout product quality and to eliminate "middle men." The result is higher value for customers, higher margins for retailers, and greater efficiency in direct communication with the manufacturer for everyone.











TOTAL PRODUCT OWNERSHIP FROM IDEA TO FINSHED PRODUCT

## UNMATCHED QUALITY CONTROL

Vanguard founders credit our success to the people across the globe who have given supportive and valuable feedback about product features and price points over our three decades. This focus on listening to the market's needs and wants has inspired us to create products with first-of-its-kind features, notable reliability, and impressive price points. Notable industry publications and media have consistently recognized our products' quality and performance. We're privileged to have earned top honors from the Technical Image Press Association, the Red Dot Design Award, iF Design Award, the Industrial Designers Association of America, Gmark, and other respected global associations





# SPORTING OPTICS KEY FEATURES

#### **HOYA** PREMIUM HOYA ED GLASS



Setting new standards with a rating of more than 95% light transmission, HOYA ED glass launches Vanguard optical design above the competition, ensuring brightness and clarity even in the lowest light.







#### RAPID FOCUS EYEPIECE

The rapid focus eyepiece can be adjusted in seconds, giving you a clear and crisp view of your target.



#### LOCKING DIOPTER RING

The diopter lets users adjust the focus to accommodate differences between each of their eyes. The diopter rings lock so that adjustments don't need to be made before each use.



#### LOW LIGHT PERFORMANCE

The fully multicoated lenses improve light transmission for bright and clear images, with greater low-light performance.



#### PREMIUM ED GLASS

Vanguard's Extra-low Dispersion (ED)glass significantly reduces chromatic aberrations, allowing clear, sharp viewing with high contrast.



#### MULTIGUARD® COATINGS

Vanguard's MultiGuard® coatings provide multiple layers of anti-reflective compounds resulting in optimal light transmission and producing a remarkably clear field of view.



#### **WATERPROOF & FOGPROOF**

Vanguard's O-ring seals completely prevent moisture, dust, and debris from entering the optics. Nitrogen purging prevents fogging in extreme weather



#### 2 & 3 STAGE TWIST EYE CUPS

Vanguard's twist-up eye cups come in 2 or 3 stage adjustments, allowing a customized fit for a comfortable viewing experience with or without



#### TRIPOD MOUNTABLE

With the tripod mountable feature, you can easily mount your optics to any tripod or monopod for hands-free stable viewing

# **GALLERY**









# "CHECK OUT


Vanguard listens to the voice of consumers and continuously invests in research and development to provide a great outdoor experience




**RELIABLE TRIPODS** 



**RELIABLE TRIPODS** 





**RELIABLE TRIPODS** 



**RELIABLE TRIPODS** 

TRAVELLING TRIPODS











TABLE TRIPODS TABLE TRIPODS 360° QUICK SHOE **RELIABLE TRIPODS** RELIABLE TRIPODS BINOCULAR



BINOCULARS & MONOCULARS

#### ENDEAVOR HD

The angled view Endeavor HD spotting scope combines a nitrogen-filled magnesium housing and a fully multi-coated optical system to create a well equipped zoom scope for intermediate to long-range observation. The optical system employs Extra Low Dispersion (ED) Glass to ensure accurate color rendition and virtually eliminate color fringing. The lenses are fully multicoated to ensure optimum light transmission and feature a phase-coated BAK4 roof prism. It also provides a very impressive field of view. In addition to the image quality and weather-sealed construction, the Endeavor HD includes several features that enhance the scope's functionality. It features an extendable rubber covered eyecup and boasts impressive eye relief even at the highest zoom settings. A built-in sunshield is included to eliminate glare in direct sunlight and it includes a padded raincoat with sling for carry and protection. Endeavor HD is also equipped with rapid focus and fine focus wheels for quick and precision fine tuning adjustments. The Endeavor HD mounts directly to Vanguard tripod heads (and others) that are equipped with the universal mounting plate without the use of a quick shoe.



Endeavor HD 82A

|                 | SIZE FIELD OF VIEW |   | NEAR FOCUS             | EYE RELIEF | WEIGHT           |  |
|-----------------|--------------------|---|------------------------|------------|------------------|--|
| ENDEAVOR HD 82A | 20~60 X 82         | IIO~52 FT /I,000 YDS   37~I7 M /I,000 M | 19.7~21.3 FT   6~6.5 M | 19~20 MM   | 63.8 OZ   1810 G |  |
| ENDEAVOR HD 65A | 15~45 X 65         | I44~68 FT /I,000 YDS   48~23 M /I,000 M | 14.8~18 FT   4.5~5.5 M | 19~20 MM   | 51.1 OZ   1450 G |  |



Removable Eyepiece

#### PERFECT PARTNERS **ENDEAVOR XF** OI ENDEAVOR HD 82A [PI2]

The Endeavor XF spotting scope boasts excellent optical viewing for nature enthusiasts and hunters. It features a rubber armored magnesium body and is waterproof submersible, nitrogen filled, and fogproof. The lenses are all fully multicoated to ensure optimum light transmission and feature a phasecoated BAK4. The Endeavor XF 60A comes with a 60mm objective lens and angled eyepiece with 15-45x zoom magnification. It features an extendable rubber covered eyecup and boasts impressive eye relief even at the highest zoom settings. It also provides a very impressive field of view. A built-in sunshield is included to eliminate glare in direct sunlight and it includes a padded raincoat with a sling for carrying and protection. Endeavor XF is equipped with a large smooth focusing wheel for quick focusing adjustments. The Endeavor XF mounts directly to Vanguard tripod heads (and others) that are equipped with the universal mounting plate without the use of a quick shoe. The tripod mount on the angled scope rotates to give optimum viewing angles in a variety of situations such as bench shooting and use with a window mount.



02 VEO PA-65

03 VEO 3 264A0



 Fully Multi-Coated Optics and PhaseCoated BAK4 Prism



Angled Eyepiece With


15-45X Zoom Magnification


• Built-In Lens Cap


|                 | SIZE       | FIELD OF VIEW                           | NEAR FOCUS             | EYE RELIEF | WEIGHT           |
|-----------------|------------|---|------------------------|------------|------------------|
| ENDEAVOR XF 80A | 20~60 X 80 | IIO~52 FT /I,000 YDS   37~I7 M /I,000 M | 19.7~21.3 FT   6~6.5 M | 19~20 MM   | 59.3 OZ   1680 G |
| ENDEAVOR XF 60A | 15~45 X 60 | I4I~68 FT /I,000 YDS   47~23 M /I,000 M | 16.4~19.7 FT   5~6 M   | 19~20 MM   | 45.1 OZ   1280 G |











**VEO HD** 

The VEO HD spotting scope boasts excellent optical viewing for nature enthusiasts and outdoorsmen. It is nitrogen-filled, making it waterproof/fogproof for challenging weather conditions. The lenses are all fully multi-coated to ensure optimum light transmission, and each scope equipped with a large, smooth focusing wheel for quick adjustments. The lightweight and durable carbon-composite body is well-balanced, so whether in the field or at the range, VEO HD is a must-have.



Nitrogen Filled

Waterproof & Fogproof

20~60 X 80

15~45 X 60







• 22.5mm Large Eyepiece Design



Veo HD 80A

19~20 MM

19.7~21.3 FT | 6~6.5 M

16.4~19.7 FT | 5~6 M

 Available with 60 or 80mm Objective Lens

FIELD OF VIEW

IIO~52 FT /I,000 YDS | 37~I7 M /I,000 M

141~68 FT /I.000 YDS | 47~23 M /I.000 M

Arca Swiss Compatible

Mountable to Tripod

WEIGHT

54.7 OZ | 1550 G

42.5 OZ | 1205 G

Find The Most Comfortable Viewing Angle With 180° Rotatable Front Body

PERFECT PARTNERS

OI VEO HD 80A

02 VEO PA-65

03 VEO 3T 265HABP

### **VESTA SPOTTING SCOPE KIT**

The VESTA series of spotting scopes is recommended for anyone starting out with a spotting scope, or looking for something smaller to carry with ease. To thebenefit of outdoor enthusiasts these scopes are compatible with many sized tripods. The Vesta 350 and 460 models are small enough to fit in the side pocket of a backpack and work great on a table top. Travelers and trend setters worldwide will also appreciate the Vanguard Vesta optics which are loaded with quality and deliver excellent value.



VESTA 560A

VESTA 460A

VESTA 350A

12-45X 50

• Quick Focus Adjustment Allows The User to Experience Everything in Fine-Tuned Detail

EYE RELIEF

WEIGHT

45.7 OZ | 1293 G

21.5 OZ |609 G

21.2 OZ |600 G

**NEAR FOCUS** 

26.3~29.5 FT | 8~9 M

32.8~394 FT | 10~12 M



FIELD OF VIEW

104~63 FT /I,000 YDS | 35~21 M /I,000 M

125~57 FT /I,000 YDS | 42~19 M /I,000 M

157~52 FT /I,000 YDS | 52~17 M /I,000 M 29.5~39.4 FT | 9~12 M






VESTA 460A



Model No:350A and 460A comes with Vesta TT1 Table Tripod



Model No:560A comes with VS-82



PERFECT PARTNERS

VESTA 350A







#### **ENDEAVOR ED IV**

Enhance your viewing experience with the best Endeavor ED Binocular series that Vanguard has ever produced. The innovative pairing of Premium HOYA ED (Extra-low Dispersion) glass and SK-15 Prisms allows master birders and outdoorsmen to experience nature in a totally new dimension.









- 7 layers Coatings
- Premium HOYA ED Glass **Provides A True Color Viewing** Experience
- Advanced Multi-Layer Coating Provides More Than 92% Light Transmission



Endeavor ED IV 1042

|                     | SIZE    | FIELD OF VIEW                      | NEAR FOCUS     | EYE RELIEF | ADJUST. PUPILLARY | WEIGHT          |
|---------------------|---------|------------------------------------|----------------|------------|-------------------|-----------------|
| ENDEAVOR ED IV 1042 | 10 X 42 | 340 FT /I,000 YDS   II4 M /I,000 M | 5.9 FT   I.8 M | 19 MM      | 56~74 MM          | 27.7 OZ   786 G |
| ENDEAVOR ED IV 8420 | 8 X 42  | 377 FT /I,000 YDS   I26 M /I,000 M | 5.9 FT   I.8 M | 19 MM      | 56~74 MM          | 27.7 OZ   786 G |





Advanced Multiguard® Coatings for Improved Light Transmission



Nitrogen Purged & O-Ring Sealed for 100% Fogproof & Waterproof Protection



DEDEENT DARTHER

## **ENDEAVOR ED II**

The Endeavor ED II series ushers in a new era of superior optics from Vanguard. Featuring premium HOYA ED (Extra-low Dispersion) glass, Endeavor ED Il allows for greater low-light views from dusk to dawn, providing an unforgettable experience for outdoor enthusiasts.



HOYA





 Nitrogen-Filled, Waterproof & Fogproof



• 3-Stage Twist Eyecups

 Durable MagnesiumAlloy Housing

Pebbled Rubberized Armo



DEDEFOT DARTHED

- 7 layers Coatings
- Premium HOYA ED Glass Provides A True Color Viewing Experience



Endeavor ED II 1042

|                     | SIZE    | FIELD OF VIEW                      | NEAR FOCUS   | EYE RELIEF | ADJUST. PUPILLARY | WEIGHT          |
|---------------------|---------|------------------------------------|--------------|------------|-------------------|-----------------|
| ENDEAVOR ED II 1042 | 10 X 42 | 340 FT /I,000 YDS   II4 M /I,000 M | 6.6 FT   2 M | 18 MM      | 58~74 MM          | 27.2 OZ   770 G |
| ENDEAVOR ED II 8420 | 8 X 42  | 377 FT /I,000 YDS   I26 M /I,000 M | 6.6 FT   2 M | 19.5 MM    | 58~74 MM          | 27.2 OZ   770 G |







TRIPODS & HEADS

SHOOTING SUPPORTS

#### **ENDEAVOR ED**

Endeavor ED binoculars provide outdoorsmen high-performance features at an incredible value. Extra-low Dispersion (ED) glass with MultiGuard® coatings allow for sharp, bright images even in low-light conditions.



111



 BAK4 Roof Prisms for **Enhanced Image Resolution** 

• Premium ED Glass Ensures Fine **Detail and Brilliant Colors** 



• 3-Stage Twist Eyecups

 Modern Ergonomics With an Open-Bridge Design

 Advanced Multiguard® Coatings for Higher Light Transmittance

Endeavor ED 8420

|                  | SIZE    | FIELD OF VIEW                      | NEAR FOCUS     | EYE RELIEF | ADJUST. PUPILLARY | WEIGHT          |
|------------------|---------|------------------------------------|----------------|------------|-------------------|-----------------|
| ENDEAVOR ED 1042 | 10 X 42 | 340 FT /I,000 YDS   II4 M /I,000 M | 8.2 FT   2.5 M | 16.5 MM    | 58~74 MM          | 25.8 OZ   730 G |
| ENDEAVOR ED 8420 | 8 X 42  | 367 FT /I,000 YDS   I22 M /I,000 M | 6.6 FT   2 M   | 19 MM      | 58~74 MM          | 25.8 OZ   730 G |
| ENDEAVOR ED 8320 | 8 X 32  | 377 FT /I,000 YDS   126 M /I,000 M | 6.6 FT   2 M   | 17.5 MM    | 55~74 MM          | 19.1 OZ   540 G |





PERFECT PARTNERS


OI VEO OPTIC GUARD H DLX [ PI2 ]

#### **VEO HD IV**

Vanguard's new VEO HD IV binocular series offers an upgraded viewing experience for nature lovers, birders, sports fans, and travelers. The innovative pairing of Premium HOYA ED (Extra-low Dispersion) glass and SK-15 prisms produces crystal-clear images of your subject while preserving its true image and color integrity.







FIELD OF VIEW

340 FT /I,000 YDS | II4 M /I,000 M

377 FT /I,000 YDS | I26 M /I,000 M



 Premium ED Glass Ensures Fine **Detail and Brilliant Colors** 

 Advanced Multi-Layer Coating Provides More Than 92% Light Transmission

**VEO HD IV 1042** 

**VEO HD IV 8420** 



**VEO HD IV 1042** 

EYE RELIEF ADJUST. PUPILLARY

56~74 MM

56~74 MM

• 3-Stage Twist Eyecups

 Durable Magnesium-Alloy Housing

Pebbled Rubberized Armo

Fully Waterproof Fogproof

WEIGHT 27.7 OZ | 786 G

27.7 OZ | 786 G



Center Locking Diopter Adjustment



Large Secure Focus Wheel







[ P40 ]

PERFECT PARTNERS

01 VEO HD IV 1042

VEO PA-62

04 VEO 3T 204ABP

BA-185



## VEO HD2

The VEO HD2 Binocular features HOYA extra-low dispersion (ED) glass and phase-corrected BAK4 prisms that work together to virtually eliminate chromatic aberration and produce images with true color fidelity across the entire field of view and enhanced contrast. Complementing the glass and prisms are an anti-reflective and fully multi-coated optical system that improves light transmission for bright and clear images with greater low-light performance.

| HOYA<br>GLASS |  |
|---------------|--|
|               | (a) (b) (c) (c) (c) (c) (c) (c) (c) (c) (c) (c |
| 4             |  |
| À             |  |

- 7 layers Coatings
- Phase Corrected BaK4 Roof Prisms
- Premium HOYA ED Glass Provides A True Color Viewing Experience



• 3-Stage Twist Eyecups

 Premium Mitsubishi Rubber Armor


 New Advanced **Carbon Composite** Material

VEO HD 2 1042

|                      | SIZE    | FIELD OF VIEW                      | NEAR FOCUS | EYE RELIEF | ADJUST. PUPILLARY | WEIGHT          |
|----------------------|---------|------------------------------------|------------|------------|-------------------|-----------------|
| <b>VEO HD 2</b> 1042 | 10 X 42 | 340 FT /I,000 YDS   II4 M /I,000 M | 6.5 FT 2M  | 18 MM      | 58~74 MM          | 25.4 OZ   720 G |
| <b>VEO HD 2</b> 8420 | 8 X 42  | 374 FT /I,000 YDS   I24 M /I,000 M | 6.5 FT 2M  | 19 MM      | 58~74 MM          | 25.4 OZ   720 G |



Soft Grip Center Focusing Wheel for Comfortable Viewing



PERFECT PARTNERS

03 VEO 2SAM-234TBP50T [ P40 ]

01 VEO HD 2 1042

02 VEO PA-62

03 BA-185

### **VEO HD 2 1042M**

The VEO HD2 Monocular features HOYA extra-low dispersion (ED) glass to virtually eliminate chromatic aberration and produce images with true color fidelity across the entire field of view and enhanced contrast. The package includes a smartphone adapter and bluetooth remote so you can capture crisp, clear images on the go





|                | SIZE    | FIELD OF VIEW                      | NEAR FOCUS | EYE RELIEF | WEIGHT          |
|----------------|---------|------------------------------------|------------|------------|-----------------|
| VEO HD 2 1042M | 10 X 42 | 342 FT /I,000 YDS   II4 M /I,000 M | 6.5 FT 2M  | 18 MM      | II.5 OZ   325 G |




OI VEO OPTIC GUARD WS [PI2]



• Twist-Up Eyecup

Mountable to tripod or

monopod



## **VEO HD**

The VEO HD Binocular features extra-low dispersion (ED) glass and phase-corrected BAK4 prisms that work together to virtually eliminate chromatic aberration and produce images with true color fidelity across the entire field of view and enhanced contrast. Complementing the glass and prisms are an anti-reflective and fully multi-coated optical system that improves light transmission for bright and clear images with greater low-light performance.



• 7 layers Coatings

 Phase Corrected BaK4 Roof Prisms

• Extra-Low Dispersion (ED) Glass



Large Eyepiece

• 3-Stage Twist Eyecups

 New advanced carbon composite material

VEO HD 1042

|                    | SIZE    | FIELD OF VIEW                      | NEAR FOCUS   | EYE RELIEF | ADJUST. PUPILLARY | WEIGHT          |
|--------------------|---------|------------------------------------|--------------|------------|-------------------|-----------------|
| <b>VEO HD</b> 1042 | 10 X 42 | 342 FT /I,000 YDS   II4 M /I,000 M | 6.6 FT   2 M | 18 MM      | 58~74 MM          | 27.1 OZ   767 G |
| <b>VEO HD</b> 8420 | 8 X 42  | 372 FT /I,000 YDS   I24 M /I,000 M | 6.6 FT   2 M | 19 MM      | 58~74 MM          | 26.8 OZ   760 G |



**Ergonomic Thumb Position** 



PERFECT PARTNERS

01 VEO HD 1042

03 VEO 3GO 203AP

02 VEO PA-62

03 BA-185

#### **VEO ED**

VEO ED is a well-balanced, lightweight, and durable carbon-composite binocular. It is 100% waterproof/fogproof, and designed to take on challenging weather conditions. Extra Low Dispersion (ED) Glass effectively reduces chromatic aberration and enhances color resolution and contrast. The VEO ED is essential for every outdoor enthusiast.





4 layers Coatings

Waterproof and Fogproof

• Extra-Low Dispersion (ED) Glass



**Textured Rubber Armor** 

 Phase Corrected BaK4 Roof Prisms

| VFO | FD  | 105 |
|-----|-----|-----|
| VEC | ודו | 1/2 |

|                    | SIZE    | FIELD OF VIEW                      | NEAR FOCUS      | EYE RELIEF | ADJUST. PUPILLARY | WEIGHT          |
|--------------------|---------|------------------------------------|-----------------|------------|-------------------|-----------------|
| VEO ED 1250        | 12 X 50 | 25I FT /I,000 YDS   84 M /I,000 M  | II.5 FT   3.5 M | 18 MM      | 60~75 MM          | 26.8 OZ   760 G |
| <b>VEO ED</b> 1050 | 10 X 50 | 282 FT /I,000 YDS   94 M /I,000 M  | 9.8 FT 3 M      | 19 MM      | 59.5~75 MM        | 27.6 OZ   782 G |
| <b>VEO ED</b> 1042 | 10 X 42 | 314 FT /1,000 YDS   105 M /1,000 M | 9.2 FT   2.8 M  | 16 MM      | 55~75 MM          | 22.6 OZ   640 G |
| VEO ED 8420        | 8 X 42  | 330 FT /I,000 YDS   IIO M /I,000 M | 8.2 FT   2.5 M  | 19 MM      | 55~75 MM          | 22.6 OZ   640 G |




**Oversized Center Focus** Wheel For Easy Control



VEO PA-62 BA-185

04 VEO 3GO 203AP





## **VEO ED 8420M**

Vanguard's new VEO ED 8420M monocular offers a new, compact way for you to get a closer look in the field or at events. This 100% waterproof and fogproof optics piece features Extra-Low Dispersion (ED) Glass, which effectively reduces chromatic aberration and enhances color resolution and contrast. The package includes VEO PA-62 smartphone adapter and Bluetooth remote, so you can capture your magnified subjects on film or video.



 Waterproof and Fogproof

**VEO ED 8420M** 

FIELD OF VIEW

8 X 42 324 FT /I,000 YDS | 108 M /I,000 M



EYE RELIEF

19 MM

NEAR FOCUS

8.2 FT | 2.5 M

WEIGHT

10.6 OZ | 300 G





# **VEO XF**

PERFECT PARTNERS

OI VEO OPTIC GUARD WS [ PI2 ]

VEO ED is a well-balanced, lightweight, and durable carbon-composite binocular. It is 100% waterproof/fogproof, and designed to take on challenging weather conditions. Extra Low Dispersion (ED) Glass effectively reduces chromatic aberration and enhances color resolution and contrast. The VEO ED is essential for every outdoor enthusiast.



- 4 layers Coatings
- Waterproof and Fogproof
- Extra-Low Dispersion (ED) Glass



| EO XF |
|-------|
|-------|

|             | SIZE    | FIELD OF VIEW                      | NEAR FOCUS     | EYE RELIEF | ADJUST. PUPILLARY | WEIGHT |
|-------------|---------|------------------------------------|----------------|------------|-------------------|--------|
| VEO XF 1042 | 10 X 42 | 332 FT /I,000 YDS   III M /I,000 M | 6.9 FT   2.1 M | 16 MM      | 57~74 MM          | -      |
| VEO XF 8420 | 8 X 42  | 409 FT /I,000 YDS   136 M /I,000 M | 6.9 FT   2.1 M | 20 MM      | 57~74 MM          | -      |



Vesta binoculars are designed for any birder, traveller or hunter who is looking for value for money, without compromising on performance. The Vesta binoculars contain optical quality glass with an enhancing BAK4 roof prism design and multi-coating technology for crisp resolution, clarity, color fidelity and light transmission. Each binocular is manufactured and assembled with a light weight yet durable housing, and is waterproof and fogproof. The large center focus knob allows the user to experience everything in fine-tuned detail. From the packaging to the product and accessories, these new binoculars deliver the impression of a quality design while always remaining focused onperformance and most importantly your success afield.



**VESTA** 

Ergonomic and Durable Body

• Light Weight yet Durable Housing



Twist Out Rubber Eyecups For Comfortable Viewing

PERFECT PARTNERS

OI VEO OPTIC GUARD H [PI2]

**VESTA 8420** 

BAK Roof Prisms

|                   | SIZE    | FIELD OF VIEW                      | NEAR FOCUS     | EYE RELIEF | ADJUST. PUPILLARY | WEIGHT          |
|-------------------|---------|------------------------------------|----------------|------------|-------------------|-----------------|
| <b>VESTA</b> 1042 | 10 X 42 | 298 FT /I,000 YDS   100 M /I,000 M | 6.9 FT   2.1 M | 17 MM      | 56~74 MM          | 20.8 OZ   590 G |
| VESTA 1025        | 10 X 25 | 330 FT /I,000 YDS   IIO M /I,000 M | 8.2 FT  2.5 M  | 10 MM      | 56~74 MM          | 9.88 OZ   280 G |
| VESTA 8420        | 8 X 42  | 325 FT /I,000 YDS   108 M /I,000 M | 6.9 FT 2.IM    | 19 MM      | 56~74 MM          | 21.5 OZ   610 G |
| VESTA 8250        | 8 X 25  | 340 FT /I,000 YDS   II4 M /I,000 M | 8.2 FT   2.5 M | 12.5 MM    | 56~74 MM          | 9.88 OZ   280 G |



and Smooth Ease of use

## **VESTA 8320M**

The Vanguard Vesta 8320M monocular delivers optimal optical performance in a lightweight and compact body. The package includes a smart phone adapter and blue tooth remote so you can capture crisp, clear images on the go.



8.8 OZ | 250 G

|             | SIZE   | FIELD OF VIEW                      | NEAR FOCUS   | EYE RELIEF |
|-------------|--------|------------------------------------|--------------|------------|
| VESTA 8320M | 8 X 32 | 392 FT /I,000 YDS   131 M /I,000 M | 6.6 FT   2 M | 17.7 MM    |









## **OPTICS ACCESSORIES**

#### **VEO PA-65**

VEO PA-65 is a universal smartphone digiscoping kit that will fit any smartphone up to 3.54inches/90mm wide, and can be used with almost any spotting scope from any brand to enable you to take captivating closeup shots and share them straight to social media

Fits smartphones up to: 59-90mm/2.3-3.5in.wide Fits eye pieces between:  $\phi$ 34-54mm/1.3-2.1in.



#### **VEO PA-62**

VEO PA-62 universal digiscope adaptor can be used for taking photos or video with almost any smartphone up to 91mm/3.6 inches wide, with an adjustable arm that can be aligned to any lens on the camera. It quickly attaches to the eyepiece of any binocular or monocular that has a diameter between 41.5-44.7mm/1.6-1.8 inches wide, and can be paired to Apple or Android smartphones with the included Bluetooth remote for touch-free control.

Fits smartphones up to: 60-91mm/2.4-3.6in.wide Fits eye pieces between:  $\phi 41.5$ -44.7mm/1.6-1.8in



#### **BA-185**

The BA-185 Binocular Tripod Adapter steadies a binocular for clear, relaxed, hands-free viewing. It works with any roof prism binocular that has a standard 1/4-20 thread tripod socket, and on most models its thin bridge will still allow you to set your binocular to the minimum interpupillary distance adjustment





#### **OPTIC GUARD ACCESSORIES**

The VEO OPTIC GUARD series is the quintessential harness solution for passionate birders who use their binoculars or cameras for extended periods. The Optic Guard is designed with ultimate ergonomic comfort in mind, enabling you carry your gear in the field without added weight or pressure. Whether you're just heading out for a short hike or committed to a long-term birding experience, the VEO OPTIC GUARD series is sure to enhance your outdoor experience.

#### **VEO OPTIC GUARD H DLX**

Strapwidth: 1.0 inches/25 mm Maxload: 5.5 Lbs/2.5 kg Weight: 0.53 Lbs/240 g








#### **VEO OPTIC GUARD H**

Strapwidth: 1.0 inches/25 mm Maxload: 2.2 Lbs/1 kg Weight: 0.31 Lbs/140 g








#### **VEO OPTIC GUARD WS**

Strapwidth: 1.0 inches/25 mm Maxload: 4Lbs/1.8 kg Weight: 0.1 Lbs/40 g



Bonus cinch clip







**VEO 3** AV/CV 20

The VEO 3 tripods are designed for every outdoorsman who is looking for maximum stability and function in more challenging conditions. We have introduced easy to clean leg locks to maximize the life of the tripod with easy and efficient maintenance. One leg allows for conversion to a monopod



| ALUMINUM      | FOLDED HEIGHT [IN/MM] | EXTENDED HT. | STANDARD HT. | LEG DIAM. | LEG SECT. | HEAD      | MAX LOAD<br>[LBS / KG] | WEIGHT<br>[LBS/G] |
|---------------|-----------------------|--------------|--------------|-----------|-----------|-----------|------------------------|-------------------|
| VEO 3 303AV20 | 28.4 / 722            | 71.3 / 1810  | 57.9 / 1472  | 30        | 3         | VEO PV-20 | 13.2 / 6               | 7.1 / 3241        |
| CARBON FIBER  |                       |              |              |           |           |           |                        |                   |
| VEO 3 303CV20 | 28.4 / 722            | 71.3 / 1810  | 57.9 / 1472  | 30        | 3         | VEO PV-20 | 13.2 / 6               | 6.4 / 2894        |





#### **VEO 3** AV/CV 18

The VEO 3 tripods are designed for every outdoorsman who is looking for maximum stability and function in more challenging conditions. We have introduced easy to clean leg locks to maximize the life of the tripod with easy and efficient maintenance. One leg allows for conversion to a



| ALUMINUM      | FOLDED HEIGHT<br>[IN/MM] | EXTENDED HT. [IN/MM] | STANDARD HT. [IN/MM] | LEG DIAM. | LEG SECT. | HEAD      | MAX LOAD<br>[LBS / KG] | WEIGHT<br>[LBS/G] |
|---------------|--------------------------|----------------------|----------------------|-----------|-----------|-----------|------------------------|-------------------|
| VEO 3 303AVI8 | 28.4 / 722               | 71.3 / 1810          | 57.9 / 1472          | 30        | 3         | VEO PV-20 | 13.2 / 6               | 7.1 / 3241        |
| CARBON FIBER  |                          |                      |                      | : A       | 1,59      |           |                        |                   |
| VEO 3 303CV18 | 28.4 / 722               | 71.3 / 1810          | 57.9 / 1472          | 30        | 3         | VEO PV-20 | 13.2 / 6               | 64 / 2894         |
|               |                          |                      |                      |           |           |           |                        |                   |













## **VEO 3** AV/CV 16

The VEO 3 tripods are designed for every outdoorsman who is looking for maximum stability and function in more challenging conditions. We have introduced easy to clean leg locks to maximize the life of the tripod with easy and efficient maintenance. One leg allows for conversion to a



| ALUMINUM         | FOLDED HEIGHT<br>[IN/MM] | EXTENDED HT. [IN / MM] | STANDARD HT. [IN/MM] | LEG DIAM. | LEG SECT. | HEAD      | (LBS / KG) | WEIGHT<br>[LBS/G] |
|------------------|--------------------------|------------------------|----------------------|-----------|-----------|-----------|------------|-------------------|
| VEO 3 263AVI6    | 28.4 / 722               | 71.3 / 1810            | 57.9 / 1472          | 30        | 3         | VEO PV-20 | 13.2 / 6   | 7.1 / 3241        |
| VEO 3 264AVI6    | 28.4 / 722               | 71.3 / 1810            | 57.9 / 1472          | 30        | 3         | VEO PV-20 | 13.2 / 6   | 7.1 / 3241        |
| VEO 3 263AVI6LVL | 28.4 / 722               | 71.3 / 1810            | 57.9 / 1472          | 30        | 3         | VEO PV-20 | 13.2 / 6   | 7.1 / 3241        |
| CARBON FIBER     |                          |                        |                      |           |           |           |            |                   |
| VEO 3 263CVI6    | 28.4 / 722               | 71.3 / 1810            | 57.9 / 1472          | 30        | 3         | VEO PV-20 | 13.2 / 6   | 64/2894           |

284/722 7I.3/I8I0 57.9/I472 30 3 VEO PV-20 I3.2/6 64/289

| PERFECT PARTNERS |                          |                    |
|------------------|--------------------------|--------------------|
| SS               | OI ENDEAVOR HD 82A [PI2] | 02 VEO PA-65 [PI2] |




#### **VEO 3** AV/CV 15

The VEO 3 tripods are designed for every outdoorsman who is looking for maximum stability and function in more challenging conditions. We have introduced easy to clean leg locks to maximize the life of the tripod with easy and efficient maintenance. One leg allows for conversion to a



| ALUMINUM      | FOLDED HEIGHT [IN/MM] | EXTENDED HT. [IN/MM] | STANDARD HT. [IN/MM] | LEG DIAM. | LEG SECT. | HEAD            | MAX LOAD<br>[LBS / KG] | WEIGHT<br>[LBS/G] |
|---------------|-----------------------|----------------------|----------------------|-----------|-----------|-----------------|------------------------|-------------------|
| VEO 3 264AVI5 | 22.6 / 575            | 61.2 / 1555          | 48.3 / 1227          | 26        | 4         | VEO PV-15       | 11/5                   | 5.3 / 2400        |
| CARBON FIBER  | 9-23                  |                      |                      |           |           | Ka <sup>2</sup> |                        |                   |
| VEO 3 264CVI5 | 22.6 / 575            | 61.2 / 1555          | 48.3 / 1227          | 26        | 4         | VEO PV-15       | 11/5                   | 4.8 /2200         |







#### VEO 3 AB/CB

The VEO 3 tripods are designed for every outdoorsman who is looking for maximum stability and function in more challenging conditions. We have introduced easy to clean leg locks to maximize the life of the tripod with easy and efficient maintenance. One leg allows for conversion to a monopod



| ALUMINUM     | FOLDED HEIGHT [IN/MM] | EXTENDED HT. [IN/MM] | STANDARD HT. | LEG DIAM. | LEG SECT. | HEAD        | MAX LOAD<br>[LBS / KG] | WEIGHT [LBS/G] |
|--------------|-----------------------|----------------------|--------------|-----------|-----------|-------------|------------------------|----------------|
| VEO 3 303AB  | 29.3 / 745            | 72.1 / 1831          | 58.8 / 1495  | 30        | 3         | VEO BH-250S | 55.1 / 25              | 5.7 / 2585     |
| VEO 3 304AB  | 26.2/665              | 71.9 / 1826          | 58.8 / 1494  | 30        | 4         | VEO BH-250S | 55.1 / 25              | 5.7 / 2586     |
| VEO 3 263AB  | 29.1 / 738            | 70.7 / 1795          | 57.7 / 1465  | 26        | 3         | VEO BH-160S | 33.1 / 15              | 4.7 / 2142     |
| CARBON FIBER |                       |                      |              |           |           |             |                        |                |
| VEO 3 303CB  | 29.3 / 745            | 72.1 / 1831          | 58.8 / 1495  | 30        | 3         | VEO BH-250S | 55.1 / 25              | 4.9 / 2238     |
| VEO 3 304CB  | 26.2/665              | 71.9 / 1826          | 58.8 / 1494  | 30        | 4         | VEO BH-250S | 55.1 / 25              | 4.98 / 2259    |
| VEO 3 263CB  | 29.1 / 738            | 70.7 / 1795          | 57.7 / 1465  | 26        | 3         | VEO BH-160S | 33.1 / 15              | 4.2 / 1900     |





#### **VEO 3** AO/CO

The VEO 3 tripods are designed for every outdoorsman who is looking for maximum stability and function in more challenging conditions. We have introduced easy to clean leg locks to maximize the life of the tripod with easy and efficient maintenance. One leg allows for conversion to a



| ALUMINUM     | FOLDED HEIGHT [IN/MM] | EXTENDED HT. [IN/MM] | STANDARD HT. | LEG DIAM. | LEG SECT. | HEAD      | MAX LOAD<br>[LBS / KG] | WEIGHT<br>[LBS/G] |
|--------------|-----------------------|----------------------|--------------|-----------|-----------|-----------|------------------------|-------------------|
| VEO 3 263A0  | 27.9 / 708            | 69.4 / 1763          | 56.4 / 1432  | 26        | 3         | VEO PH-28 | 17.6 / 8               | 5.2 / 2360        |
| VEO 3 264AO  | 22.6 / 575            | 61.2 / 1555          | 48.3 / 1227  | 26        | 4         | VEO PH-28 | 17.6 / 8               | 5.1 / 2320        |
| VEO 3 233AO  | 25 / 636              | 61.2 / 1555          | 49.2 / 1250  | 23        | 3         | VEO PH-26 | 13.2 / 6               | 4.1 / 1860        |
| CARBON FIBER |                       |                      |              |           |           |           |                        |                   |
| VEO 3 263CO  | 27.9 / 708            | 69.4 / 1763          | 56.4 / 1432  | 26        | 3         | VEO PH-28 | 17.6 / 8               | 4.6 / 2100        |
| VEO 3 264CO  | 22.6 / 575            | 61.2 / 1555          | 48.3 / 1227  | 26        | 4         | VEO PH-28 | 17.6 / 8               | 4.7 / 2120        |
| VED 3 23300  | 25 / 636              | 61.2 / 1555          | 49.2 / 1250  | 23        | 3         | VEO PH-26 | 13.2 / 6               | 3.7 / 1680        |









Rubber feet & Spiked feet

Arca Compatible 2-Way Pan

VEO PH-28/26



Leg that converts to a monopod

#### **VEO 3T** BALL HEAD WITH REMOVABLE PAN HANDLE

FOLDED HEIGHT EXTENDED HT. STANDARD HT. LEG DIAM.
[IN/MM] [IN/MM] [IN/MM] [MM]

The VEO 3T Series is designed to deliver both portability (with models that fold to less than 16 in/41cm and weigh 3lbs/1.4kg) and performance (with a maximum height of up to 65 in/166cm and a load capacity of up to 26.5lbs/12kg). The series also include an Arca-compatible head and a quick-release plate that has the option to attach a pan-handle for greater control, especially when using longer lenses or spotting scopes, and a quick release plate that can be used to attach a smartphone up to 3.35 in/85mm wide with additional accessories. As if that wasn't enough, each tripod has a leg that can convert to a monopod with an all-weather TPU grip


MAX LOAD [LBS / KG]

BTT models have differences, please

refer to vanguard official website for




| VEO 3T 265HABP | 17.3 / 439 | 65.4 / 1660 | 50.2 / 1275 | 26 | 5 | VEO BP-I20T | 26.4 / 12 | 4.7 / 2115   |
|----------------|------------|-------------|-------------|----|---|-------------|-----------|--|
| VEO 3T 235ABP  | 16.1 / 410 | 61.0 / 1550 | 45.5 / 1155 | 23 | 5 | VEO BP-50T  | 17.6 / 8  | 3.8 / 1745   |
| VEO 3T 204ABP  | 15.9 / 405 | 55.1 / 1400 | 40.9 / 1040 | 20 | 4 | VEO BP-45T  | 8.8 / 4   | 3.3 / 1490   |
| VEO 3TT 233ABP | 9.7 / 245  | 22.1 / 560  | 19.1 / 486  | 23 | 3 | VEO BP-50T  | 17.6 / 8  | 2.6 / 1161   |
| VEO 3TT 203ABP | 9.1 / 225  | 19.7 /500   | 57.7 / 443  | 20 | 3 | VEO BP-45T  | 8.8 / 4   | 2.2 / 977  |
| CARBON FIBER   |            |             |             |    |   |             |           | The state of the s |
| VEO 3T 265HCBP | 17.3 / 439 | 654 / 1660  | 50.2 / 1275 | 26 | 5 | VEO BP-I20T | 26.4 / 12 | 4.2 / 1910   |
| VEO 3T 235CBP  | 16.1 / 410 | 61.0 / 1550 | 45.5 / 1155 | 23 | 5 | VEO BP-50T  | 17.6 / 8  | 3.5 / 1600   |
| VEO 3T 204CBP  | 15.9 / 405 | 55.1 / 1400 | 40.9 / 1040 | 20 | 4 | VEO BP-45T  | 8.8 / 4   | 3.0 / 1375   |
| VEO 3TT 233CBP | 97/245     | 221/560     | 191/486     | 23 | 3 | VFO BP-50T  | 176/8     | 24/1101  |





#### **VEO 3T** 2-WAY PAN HEAD WITH FOLDING HANDLE

The VEO 3T Series is designed to deliver both portability (with models that fold to less than 16 in/41cm and weigh 3lbs/1.4kg) and performance (with a maximum height of up to 65 in/166cm and a load capacity of up to 26.5lbs/12kg). The series also include an Arca-compatible head and a quick-release plate that has the option to attach a pan-handle for greater control, especially when using longer lenses or spotting scopes, and a quick release plate that can be used to attach a smartphone up to 3.35 in/85mm wide with additional accessories. As if that wasn't enough, each tripod has a leg that can convert to a monopod with an all-weather TPU grip



| ALUMINUM      | FOLDED HEIGHT [IN/MM] | EXTENDED HT. [IN/MM] | STANDARD HT. | LEG DIAM. | LEG SECT. | HEAD      | MAX LOAD<br>[LBS / KG] | WEIGHT [LBS/G] |
|---------------|-----------------------|----------------------|--------------|-----------|-----------|-----------|------------------------|----------------|
| VEO 3T 235AP  | 16.1 / 410            | 604/1535             | 44.9 / 1140  | 23        | 5         | VEO PH-20 | 13.2 / 6               | 3.6 / 1648     |
| VEO 3TT 233AP | 9.7 / 245             | 21.2 / 538           | 18.4 / 446   | 23        | 3         | VEO PH-20 | 13.2 / 6               | 24/1100        |
| CARBON FIBER  |                       | * /                  |              |           |           |           |                        |                |
| VEO 3T 235CP  | 16.1 / 410            | 60.4 /1535           | 44.9 / 1140  | 23        | 5         | VEO PH-20 | 13.2 / 6               | 3.3 / 1498     |













SHOOTING SUPPORTS

The outlook between VEO3T and VEO

3TT models have differences, please

refer to vanguard official website for

#### **VEO 3T** BALL HEAD WITH REMOVABLE PAN HANDLE

The VEO 3T Series is designed to deliver both portability (with models that fold to less than 16 in/41cm and weigh 3lbs/1.4kg ) and performance (with a maximum height of up to 65 in/166cm and a load capacity of up to 26.5lbs/12kg). The series also include an Arca-compatible head and a quick-release plate that has the option to attach a pan-handle for greater control, especially when using longer lenses or spotting scopes, and a quick release plate that can be used to attach a smartphone up to 3.35 in/85mm wide with additional accessories. As if that wasn't enough, each tripod has a leg that can convert to a monopod with an all-weather TPU grip




| ALUMINUM       | FOLDED HEIGHT [IN/MM] | EXTENDED HT. [IN/MM] | STANDARD HT. | LEG DIAM. | LEG SECT. | HEAD        | MAX LOAD<br>[LBS / KG] | WEIGHT [LBS/G] |
|----------------|-----------------------|----------------------|--------------|-----------|-----------|-------------|------------------------|----------------|
| VEO 3T 265HABP | 17.3 / 439            | 65.4 / 1660          | 50.2 / 1275  | 26        | 5         | VEO BP-120T | 26.4 / 12              | 4.7 / 2115     |
| VEO 3T 235ABP  | 16.1 / 410            | 61.0 / 1550          | 45.5 / 1155  | 23        | 5         | VEO BP-50T  | 17.6 / 8               | 3.8 / 1745     |
| VEO 3T 204ABP  | 15.9 / 405            | 55.1 / 1400          | 40.9 / 1040  | 20        | 4         | VEO BP-45T  | 8.8 / 4                | 3.3 / 1490     |
| VEO 3TT 233ABP | 9.7 / 245             | 22.1 / 560           | 19.1 / 486   | 23        | 3         | VEO BP-50T  | 17.6 / 8               | 2.6 / 1161     |
| VEO 3TT 203ABP | 9.1 / 225             | 19.7 /500            | 57.7 / 443   | 20        | 3         | VEO BP-45T  | 8.8 / 4                | 2.2 / 977      |
| CARBON FIBER   |                       |                      |              |           |           |             |                        |                |
| VEO 3T 265HCBP | 17.3 / 439            | 654 / 1660           | 50.2 / 1275  | 26        | 5         | VEO BP-120T | 26.4 / 12              | 4.2 / 1910     |
| VEO 3T 235CBP  | 16.1 / 410            | 61.0 / 1550          | 45.5 / 1155  | 23        | 5         | VEO BP-50T  | 17.6 / 8               | 3.5 / 1600     |
| VEO 3T 204CBP  | 15.9 / 405            | 55.1 / 1400          | 40.9 / 1040  | 20        | 4         | VEO BP-45T  | 8.8 / 4                | 3.0 / 1375     |
| VEO 3TT 233CBP | 9.7 / 245             | 22.1 / 560           | 19.1 / 486   | 23        | 3         | VEO BP-50T  | 17.6 / 8               | 2.4 / 1101     |





#### **VEO 3T** 2-WAY PAN HEAD WITH FOLDING HANDLE

The VEO 3T Series is designed to deliver both portability (with models that fold to less than 16 in/41cm and weigh 3lbs/1.4kg) and performance (with a maximum height of up to 65 in/166cm and a load capacity of up to 26.5lbs/12kg). The series also include an Arca-compatible head and a quick-release plate that has the option to attach a pan-handle for greater control, especially when using longer lenses or spotting scopes, and a quick release plate that can be used to attach a smartphone up to 3.35 in/85mm wide with additional accessories. As if that wasn't enough, each tripod has a leg that can convert to a monopod with an all-weather TPU grip



|      | ALUMINUM      | FOLDED HEIGHT<br>[IN/MM] | EXTENDED HT. [IN/MM] | STANDARD HT. | LEG DIAM. | LEG SECT. | HEAD      | MAX LOAD<br>[LBS / KG] | WEIGHT [LBS/G] |
|------|---------------|--------------------------|----------------------|--------------|-----------|-----------|-----------|------------------------|----------------|
| NT B | VEO 3T 235AP  | 16.1 / 410               | 60.4 /1535           | 44.9 / 1140  | 23        | 5         | VEO PH-20 | 13.2 / 6               | 3.6 / 1648     |
| 1 16 | VEO 3TT 233AP | 9.7 / 245                | 21.2 / 538           | 18.4 / 446   | 23        | 3         | VEO PH-20 | 13.2 / 6               | 24/1100        |
|      | CARBON FIBER  |                          |                      |              |           |           |           |                        |                |
|      | VEO 3T 235CP  | 16.1 / 410               | 60.4 / 1535          | 44.9 / 1140  | 23        | 5         | VEO PH-20 | 13.2 / 6               | 3.3 / 1498     |















SHOOTING SUPPORTS

#### V

#### **VEO 3GO** TRAVELLING TRIPOD

VEO 3 GO tripods recognize the fact that many shooters don't take a tripod along because the extra bulk and weight are cumbersome. This series solves this with models that fold down to as little as 13 in/33cm and weigh as little as 1.8lbs/816g making them incredibly portable, but despite this portability there are models that can extend up to 65 in/166cm and handle up to 22lbs/10kg. The feature-rich range is available in aluminum or extremely lightweight carbon fiber, both options ideal for all types of cameras from DSLR to mirrorless/CSC/hybrid cameras and even smart phones. The included smart phone holder and Bluetooth remote turn the VEO 3 GO into a tripod or monopod/selfie stick capable of capturing images remotely with your smart phone.



ALTA BH-102



| ALUMINUM       | FOLDED HEIGHT [IN / MM] | EXTENDED HT. [IN/MM] | STANDARD HT. | LEG DIAM. | LEG SECT. | HEAD        | MAX LOAD<br>[LBS / KG] | WEIGHT<br>[LBS/G] |
|----------------|-------------------------|----------------------|--------------|-----------|-----------|-------------|------------------------|-------------------|
| VEO 3GO 265HAB | 16.1 / 410              | 65.5 / 1665          | 49.6 / 1260  | 26        | 5         | ALTA BH-102 | 22/10                  | 3.6 / 1659        |
| VEO 3GO 235AB  | 12.9 / 330              | 53.5 / 1360          | 41.7 / 1060  | 23        | 5         | T-50        | 11/5                   | 2.7 / 1225        |
| VEO 3GO 204AB  | 13.6 / 345              | 51.5 / 1310          | 39.8 / 1010  | 20        | 4         | T-45        | 6.6/3                  | 2.1 / 945         |

| CAR  | RΩ | ΝI   | FIR | FR  |  |
|------|----|------|-----|-----|--|
| יוחו | Dυ | 14 1 | ID  | LIV |  |

| VEO 3GO 265HCB | 16.1 / 410 | 65.5 / 1665 | 49.6 / 1260 | 26 | 5 | ALTA BH-102 | 22/10 | 3.1 / 1415 |
|----------------|------------|-------------|-------------|----|---|-------------|-------|------------|
| VEO 3GO 235CB  | 12.9 / 330 | 53.5 / 1360 | 41.7 / 1060 | 23 | 5 | T-50        | 11/5  | 2.3 / 1065 |
| VEO 3GO 204CB  | 13.6 / 345 | 51.6 / 1310 | 39.8 / 1010 | 20 | 4 | T-45        | 6.6/3 | 1.8 / 816  |











VEO3GO235CB



Fits any smartphone up to 87mm wide





VEO 3GO 265HCB

#### **VEO 3GO** TRAVELLING TRIPOD

VEO 3 GO tripods recognize the fact that many shooters don't take a tripod along because the extra bulk and weight are cumbersome. This series solves this with models that fold down to as little as 13 in/33cm and weigh as little as 1.8lbs/816g making them incredibly portable, but despite this portability there are models that can extend up to 65 in/166cm and handle up to 22lbs/10kg. The feature-rich range is available in aluminum or extremely lightweight carbon fiber, both options ideal for all types of cameras from DSLR to mirrorless/CSC/hybrid cameras and even smart phones. The included smart phone holder and Bluetooth remote turn the VEO 3 GO into a tripod or monopod/selfie stick capable of capturing images remotely with your smart phone.



| ALUMINUM       | FOLDED HEIGHT [IN/MM] | EXTENDED HT. [IN/MM] | STANDARD HT. | LEG DIAM. | LEG SECT. | HEAD        | MAX LOAD<br>[LBS / KG] | WEIGHT<br>[LBS/G] |
|----------------|-----------------------|----------------------|--------------|-----------|-----------|-------------|------------------------|-------------------|
| VEO 3GO 235AP  | 13.4 / 340            | 53.4 /1335           | 41.6 / 1058  | 23        | 5         | VEO 2 PH-25 | 7.7 / 3.5              | 2.7 / 1239        |
| VEO 3GOT 233AP | 13.4 / 340            | 53.4 /1335           | 41.6 / 1058  | 23        | 5         | VEO 2 PH-25 | 7.7 / 3.5              | 2.7 / 1239        |
| VEO 3GOT 203AP | 13.4 / 340            | 53.4 /1335           | 41.6 / 1058  | 23        | 5         | VEO 2 PH-25 | 7.7 / 3.5              | 2.7 / 1239        |
| CARBON FIBER   |                       |                      |              |           |           |             |                        |                   |
| VEO 3GO 235CP  | 13.4 / 340            | 53.4 /1335           | 41.6 / 1058  | 23        | 5         | VEO 2 PH-25 | 7.7 / 3.5              | 24/1080           |
| VEO 3GO 204CP  | 14.2 / 360            | 52.6 /1335           | 40.1 / 1018  | 20        | 4         | VEO 2 PH-25 | 7.7 / 3.5              | 2.1 / 947         |







PPORTS

## VEO 2 PRO STANDARD TRIPOD

The VEO 2 PRO AV/CV models are designed for photography with longer lenses, videography or bird watching/hunting using a spotting scope. The 2-way pan-heads feature extra-large quick release plates and extended video handles for maximum control, and ergonomic locking knobs to control movement. With a choice of an Arca compatible head (VEO 2 PH-15) or a Vanguard quick release lever lock (VEO 2 PH-13) and a maximum load capacity of up to 5kg, these tripods deliver a solid and stable base



3/8" to 1/4" Reversible Thread



20°, 45°, 80° Adjustable Leg Angles



| ALUMINUM       | FOLDED HEIGHT | EXTENDED HT. | STANDARD HT. | LEG DIAM. | LEG SECT. | HEAD        | MAX LOAD<br>[LBS / KG] | WEIGHT<br>[LBS/G] |
|----------------|---------------|--------------|--------------|-----------|-----------|-------------|------------------------|-------------------|
| VEO 2PRO 263AO | 24 / 610      | 63 / 1600    | 50.8 / 1290  | 26        | 3         | VEO 2 PH-28 | 11/5                   | 4.24 / 1926       |
| VEO 2PRO 233AO | 22 / 560      | 57.5 / 1460  | 45.7 / 1160  | 23        | 3         | VEO 2 PH-28 | 8.8 / 4                | 3.71 / 1683       |
| VEO 2PRO 203AO | 22 / 560      | 57.5 / 1460  | 45.9 / 1165  | 20        | 3         | VEO 2 PH-26 | 6.6/3                  | 3.14 / 1425       |





## **VESTA TB**

VESTATB is a cost-effective tripod with both a simple design and advanced features. The aluminum construction is lightweight, and the inverted 4- or 5-section legs fold up for compact carrying. The legs configure to 3 angles with twist-locks for quick and easy opening and closing. A two-section center column helps increase stability and height. The sturdy ball head has large ergonomic knobs, and it includes an Arca Swiss-compatible quick-release shoe (QS-64). Shoot low-angle photos by reversing the center column.

#### Hidden hex wrench storage



| ALUMINUM       | FOLDED HEIGHT [IN/MM] | EXTENDED HT. | STANDARD HT. | LEG DIAM. | LEG SECT. | HEAD | MAX LOAD<br>[LBS/KG] | WEIGHT<br>[LBS/G] |
|----------------|-----------------------|--------------|--------------|-----------|-----------|------|----------------------|-------------------|
| VESTA TB 235AB | 14.8 / 375            | 56.3 / 1430  | 48.6 /1235   | 23        | 5         | T-51 | 9.9 / 4.5            | 2.65 / 1200       |
| VESTA TB 204AB | 14.8 / 375            | 51.1 / 1300  | 41.5 / 1055  | 20        | 4         | T-46 | 6.6/3                | 2.06 / 934        |
| CARBON FIBER   |                       |              |              |           |           | 136  |                      | 7                 |
| VESTA TB 235CB | 14.8 / 375            | 56.3 / 1430  | 48.6 / 1235  | 23        | 5         | T-51 | 9.9 / 4.5            | 2.27 / 1031       |
| VESTA TB 204CB | 14.8 / 375            | 51.1 / 1300  | 41.5 / 1055  | 20        | 4         | T-46 | 6.6/3                | 1.77 / 802        |







## **VESTA**

The Vesta Series of tripod kits, bags, and sport optics is designed for entry-level or engaging users. In this collection you will find a variety of Vesta tripod kits. Built for performance, the Vesta Series of Tripod kits have several strong features, premium build quality, and can provide you with high to low positioning while ensuring the stability of your camera, video, or sport

PH-23 2-WAY PAN HEAD




GH-45 **DUAL PANNING GRIP HEAD** 



| ALUMINUM     | FOLDED HEIGHT [IN/MM] | EXTENDED HT. [IN/MM] | STANDARD HT. | LEG DIAM.<br>[MM] | LEG SECT. | HEAD  | MAX LOAD<br>[LBS / KG] | WEIGHT<br>[LBS/G] |
|--------------|-----------------------|----------------------|--------------|-------------------|-----------|-------|------------------------|-------------------|
| VESTA 233AP  | 22.9 / 582            | 61 / 1550            | 48.1 /1221   | 23                | 3         | PH-23 | 7.7 / 3.5              | 2.8 / 1275        |
| VESTA 203AP  | 22.4 / 570            | 61 / 1550            | 48 / 1220    | 20                | 3         | PH-23 | 7.7 / 3.5              | 24/1105           |
| VESTA 203AGH | 22.4 / 570            | 61 / 1550            | 48.2 / 1255  | 20                | 3         | GH-45 | 7.7 / 3.5              | 2.5 / 1120        |
| VESTA 204AP  | 20.5 / 520            | 61 / 1550            | 49.4 / 1255  | 20                | 4         | PH-23 | 7.7 / 3.5              | 2.5 / 1132        |





## VEO PH-28/26 2-WAY PAN HEAD

The Vanguard VEO 2-way pan head that allows one-handed control for video or spotting scopes, leaving your other hand free to operate controls with ease includes a long quick shoe with safety pin that offers a double security feature and helps to prevent your camera or other equipment from accidentally falling when it is being adjusted



VEO PH-28







|                  | LATERAL TILT° | FRONTAL TILT° | ROTATION° | WEIGHT [LBS/G] | MAX LOAD [LBS/KG] |
|------------------|---------------|---------------|-----------|----------------|-------------------|
| <b>VEO PH-28</b> | 1             | ~60°~90°      | 360°      | 14 / 639.5     | 17.6 / 8          |
| <b>VEO PH-26</b> | 1             | /             | 360°      | 1.1 / 510      | 13.2 / 6          |
| <b>VEO PV-20</b> | /             | 0° TO +90°    | 360°      | 2.2 / 1096     | 13.2 / 6          |
| VEO PV-18        | /             | 0°T0+90°      | 360°      | 1.6 / 730      | 8.8 / 4           |

## VEO PV-20/18 VIDEO PAN HEAD

Spring counterbalance to help operate heavy equipment. Smooth pan and tilt. Long handle for greater precision and torque. Magnesium alloy construction.







VEO PV-18

QS-61P

SHOOTING SUPPORTS

## **VEO CP KIT** VEO CP-65 KIT/VEO CP-46 KIT/VEO SPH

Clamp + Magic Arm + Smartphone Holder = Your camera/smartphone can be connected to many objects around you, more shooting angles, and capture wonderful moments.

#### **VEO CP-65 KIT**







## **VEO CP-46 KIT**



46 mm Clamp



Support Arm M



Smartphone Holder







|          | LENGTH<br>[IN/MM] | WIDTH<br>[IN/MM] | HEIGHT<br>[IN/MM] | MAX LOAD<br>[LBS / KG] | WEIGH<br>[LBS/G] | SIZE RANGE<br>[IN/MM] |
|----------|-------------------|------------------|-------------------|------------------------|------------------|-----------------------|
| VEO CP65 | 3.3 / 82.5        | 0.8 / 20         | 3.5 / 89          | 5.5 /2.5               | 0.4 / 159        | 2.6 / 65              |
| VEO CP46 | 2.7 / 68          | 0.8 / 20         | 3.3 / 82.5        | 3.3 /1.5               | 0.3 / 132        | 1.8 / 46              |
| VEO SPH  | 3.6 / 91          | 3.1 / 78         | 4.3 / 110         | -                      | 0.4 / 181        | 2.2-3.5 / 57-90       |

## **VEO QS-360** ARCA-COMPATIBLE 360° QUICK SHOE

Clamp + Magic Arm + Smartphone Holder = Your camera/smartphone can be connected to many objects around you, more shooting angles, and capture wonderful moments.



VEO QS-360







## **VEO LVL-60** ARCA-COMPATIBLE 360° QUICK SHOE

Clamp + Magic Arm + Smartphone Holder = Your camera/smartphone can be connected to many objects around you, more shooting angles, and capture wonderful moments.



VEO LVL-60



Can be rotated to adjust



3/8" to 1/4" adapter








#### ENDEAVOR GM-70/303AGM/303CGM/T263AGM

Clamp + Magic Arm + Smartphone Holder = Your camera/smartphone can be connected to many objects around you, more shooting angles, and capture wonderful moments.





djustable Leg Angle



Quick Shoe System for ast Firearm Attachment

|                | LENGTH    | WIDTH    | HEIGHT   | MAX LOAD   | WEIGHT    |
|----------------|-----------|----------|----------|------------|-----------|
|                | [IN/MM]   | [IN/MM]  | [IN/MM]  | [LBS / KG] | [LBS/G]   |
| ENDEAVOR GM-70 | 5.6 / 143 | 3.9 / 99 | 3.8 / 98 | 55.1 / 25  | 1.8 / 815 |

|                  | FOLDED HEIGHT [IN/MM] | EXTENDED HT. | LEG DIAM. | MAX LOAD<br>[LBS / KG] | WEIGHT<br>[LBS/G] |
|------------------|-----------------------|--------------|-----------|------------------------|-------------------|
| ENDEAVOR 303AGM  | 33.3 / 845            | 70.3 / 1785  | 30        | 55.1 / 25              | 7.1 / 3240        |
| ENDEAVOR 303CGM  | 33.3 / 845            | 70.3 / 1785  | 30        | 55.1 / 25              | 6.3 / 2855        |
| ENDEAVOR T263AGM | 12.7 / 325            | 27 / 685     | 17        | 0.9 / 430              | 0.9 / 430         |



TRIPODS & HEADS

## **EQUALIZER**

Featuring rapid deployment and un beatable stability, the equalizer series takes on an array of terrains with feet that convert from metal spikes to rubber. Models enable various shooting positions from prone to sitting or kneeling

#### **EQUALIZER QS**

Equalizer QS has a picatinny rail system that allows shooters to attach and detach firearms faster than ever. Hunters appreciate its quick leg deployment. Its Pull and Position leg adjustment system enables you to quickly and safely reposition. A buffer spring reduces shock and vibration while providing a solid shooting base.



Solid Shooting



Quick Shoe System for Fast Firearm Attachment

#### **EQUALIZER**

Compact and lightweight, Equalizer is a big hit for those wanting a pivoting bipod with a low profile for quick deployment. It has a unique Pull and Position leg adjustment system that enables you to quickly and safely reposition. Metal spiked feet easily convert to rubber and provide extra stability in multiple terrains.



Easy Pull & Position Leg Adjustment System



-30° to +30° Swing



**Buffer Spring Provides** Solid Shooting

|                      | FOLDED HEIGHT | EXTENDED HT. [IN / MM] | LEG DIAM. | WEIGHT<br>[LBS/G] |
|----------------------|---------------|------------------------|-----------|-------------------|
| <b>EQUALIZER</b> IQS | 6.9 / 176     | 10 / 255               | 14        | 0.7 / 320         |
| <b>EQUALIZER</b> 20S | II / 277      | 28 / 715               | 17        | 1/453             |
| EQUALIZER 2          | 12.7 / 325    | 27 / 685               | 17        | 0.9 / 430         |



The VEO2 shooting stick is perfect for kneeling or standing when shooting a gun or crossbow. The 1/4"-20 thread can be used to support cameras, spotting scopes, binoculars, range finders, and GoPro's.





**U-YOKE** Fins provide ultra secure grip On firearm

|                        | FOLDED HEIGHT<br>[IN/MM] | EXTENDED HT. [IN/MM] | LEG DIAM.<br>[MM] | WEIGHT<br>[LBS/G] |
|------------------------|--------------------------|----------------------|-------------------|-------------------|
| <b>VEO 2 AM-</b> 234TU | 24.4 / 620               | 62.6 / 1590          | 23                | 1.95 / 885        |
| <b>VEO 2 CM-</b> 234TU | 24.4 / 620               | 62.6 / 1590          | 23                | 1.78 / 809        |



## **QUEST**

Quest is an all in one durable shooting stick. Quest helps you handle the elements with a soft foam, contoured hand grip and anti-slip rubber feet. It's removeable U-shaped yoke with rubber fins swivels 360° so you can make shots at every angle without repositioning the shooting stick. Remove the U-shaped yoke and use its universal ¼ thread bolt with spotting scopes or cameras.



360° "U" Yoke Provides Ultra Secure Grip



Leg Brace w/ 360° Positioning (Quest T62U only)



All Weather Foam Grips

|                   | FOLDED HEIGHT [IN/MM] | EXTENDED HT. [IN/MM] | LEG DIAM. | WEIGHT<br>[LBS/G] |
|-------------------|-----------------------|----------------------|-----------|-------------------|
| <b>QUEST</b> T62U | 27.5 / 700            | 62 / 1575            | 20        | 2.2 / 1000        |
| <b>QUEST</b> M49  | 22 / 560              | 49 / 1245            | 20        | 0.66 / 300        |
| QUEST M62         | 26.3 / 670            | 62 / 1575            | 20        | 0.77 / 350        |
| QUEST B38         | 19.1 / 485            | 38 / 965             | 20        | 1.14 / 520        |
| QUEST B62         | 27.1 / 690            | 62 / 1575            | 20        | 1.43 / 650        |



## SCOUT

Made of lightweight and durable aluminum alloy, Scout is designed for on-the-go hunters. Its V-shaped yoke is rubber-lined for greater stability for your gun, and it swivels 360 degrees for shots from any angle. Quick flip leg locks make height adjustment quick and easy. Available as a bipod or monopod.




360° "V" Yoke Provides Ultra Secure Grip





All Weather Foam Grips





### **VEO 2 WINDOW MOUNTS**

With the new VEO2 window mounts by Vanguard you can cover miles of country without missing any of the details. Comfortable and smooth viewing is attained by the superior mechanical design and quality components engineered into these window mounts. Two models are available to accommodate the user's preference of either a pan head or a rotating ball head design.





VE02 BH-50WM



Strong Clamp Grip

VEO2 PH-28WM

## PH WINDOW MOUNTS

No tripod? PH pan head window mounts have unique bases and non-slip platforms. They easily attach to vehicle windows, tripods, tubular structures, blinds and others, enabling steady use of cameras, camcorders or spotting scopes for effortless panning



|              | LATERAL TILT° | FRONTAL TILT° | ROTATION° | WEIGHT<br>[LBS/G] | MAX LOAD<br>[LBS / KG] |
|--------------|---------------|---------------|-----------|-------------------|------------------------|
| VEO2 PH-28WM | /             | -60° TO +90°  | 360°      | 1.5 / 711         | 8.8 / 4                |
| VEO2 BH-50WM | -91° TO +40°  | /             | 360°      | 14 / 675          | II / 5                 |
| PH 304       | +90° TO -60°  | 0°T0+90°      | 360°      | 1.6 / 730         | 8.8 / 4                |
|              |               |               |           |                   | A3 11 1 1              |

PH 304



#### PORTA-AIM PORTABLE GUN REST

Constructed of rugged aluminum, the Porta-Aim gun rest provides stable shooting support in an easily portable device for the fast-action hunter. Porta-Aim enables users to get on target—and stay there—with a 360-degree swiveling bag.







**Anti-Vibration Pillow** 

Quick Single-Handed Height Adjustment Ring

|           | LENGTH<br>[IN/MM] | WIDTH<br>[IN/MM] | HEIGHT<br>[IN/MM] | WEIGHT<br>[LBS/G] |  |
|-----------|-------------------|------------------|-------------------|-------------------|--|
| PORTA-AIM | 12.2 / 310        | 5.7 / 145        | 8.8-12.6 /225-320 | 1.7 / 798         |  |

#### **ESPOD CX** TABLE TRIPOD

The Vanguard Espod CX 1 is a compact table tripod that is ideal for backpackers and outdoor enthusiasts. It securely holds cameras and spotting scopes up to 5.5 lb yet maintains a lightweight design so you can tote it with you on a hike or hunt. It has a two-way pan head and easy-adjust aluminum alloy 3-section legs with quick release lever locks. It has a black finish and rubber feet.





Quick Release Quick Shoe (1OS Model)



Quick Flip Leg Locks

|               | FOLDED HEIGHT<br>[IN/MM] | EXTENDED HT. [IN/MM] | LEG SECT. | MAX LOAD<br>[LBS / KG] | WEIGHT<br>[LBS/G] |
|---------------|--------------------------|----------------------|-----------|------------------------|-------------------|
| ESPOD CX I    | 11.6 / 295               | 21.3 / 540           | 3         | 5.5 / 2.5              | 1.47 /66          |
| ESPOD CX I OS | 14.8 / 375               | 24.4 / 620           | 3         | 6.6/3                  | 2.1 / 93          |
|               |                          |                      |           |                        |                   |



## **VESTATTI**

The VESTA TT1 aluminum table top tripod kit with smart phone holder is a small, ergonomic, stable table top tripod capable of holding smartphones, sport optics, and supporting cameras up to 2kg/4.4 lbs





4 Color options



Multi-angle viewing Or shooting

**VS-82** 

The VS-82 is a compact, lightweight and convenient to use tabletop tripod. Its 2-way panhead and 360 degree rotation are ideal for spotting scope use.







Adjustable Center Column

360° Swiveling 2-way Pan Head

|           | FOLDED HEIGHT<br>[IN/MM] | EXTENDED HT. [IN / MM] | MAX LOAD<br>[LBS / KG] | WEIGHT<br>[LBS/G] |  |
|-----------|--------------------------|------------------------|------------------------|-------------------|--|
| VESTA TTI | 6.89 / 175               | 3.94 / 100             | 44/2                   | 0.34 /156         |  |
| VS-82     | 10 / 255                 | 9.25 / 235             | 5.5 / 2.5              | 0.94 / 430        |  |



QS quick release plates make attaching and removing your camera a breeze, securely keeping your gear in position.

## **QS-72T**

■ Arca Swiss compatible with built in Smartphone holder







#### **QS-65**

- 1/4" camera screw & pin with D-ring
- Arca-compatible



#### QS-7IP

- 1/4" camera screw & pin with D-ring
- Arca-compatible

**QS-67** 

■ Arca-compatible

D-ring



■ 1/4" camera screw & pin with

#### QS-61P

■ 1/4" camera screw & pin with D-ring



- Arca-compatible



#### **QS-60 V2**

- 1/4" camera screw & pin with D-ring
- Arca-compatible



#### **QS-36**

■ 1/4" camera screw & pin with D-ring



#### **QS-29**

- Anti-slip rubber pad
- 1/4" camera screw with D-ring





## **ENDEAVOR SLINGS**

#### 203B/203C/20IB/20IG

- 3"+ Wide Shoulder Pad provides all-day comfort
- Shoulder pad is durable yet flexible to reduce shoulder pressure
- Anti-Slip Texture and Thicker Pad for better carrying experience
- Thumb loop for easy transport
- Quick Adjustable ladder lock buckle to sling length up to 44 inches
- 203B/203C Pockets for Mini-Tool Knife, MiniFlash Light and Other Accessories
- Rust Resistant Quick Detach/Attach Swivel hardware included

#### 150G/101B/101C

- Shoulder pad is durable yet flexible to reduce shoulder pressure
- Anti-Slip Material for better carrying experience
- Thumb loop for easy transport
- Quick Adjustable ladder lock buckle to sling length up to 45.25 inches
- "W type" heavy duty reinforced sewn ends
- Rust Resistant Quick Detach/Attach Swivel hardware included

- High Density Rubber Armored Strap
- Durable, Lightweight, Anti-Slip, Anti-Scratch and All Weather Proof
- Thumb loop for easy transport
- Quick Adjustable ladder lock buckle to sling length up to 45.25 inches
- "Z" style construction allows for maximum grip and flexibility
- Could work properly as low -40° F to as high 185° F
- Rust Resistant Quick Detach/Attach Swivel hardware included



|     |                        | SIZE       | FIELD OF VIEW                           | NEAR FOCUS             | EYE RELIEF | WEIGHT           |
|-----|------------------------|------------|---|------------------------|------------|------------------|
| SP  | ENDEAVOR HD 82A        | 20~60 X 82 | IIO~52 FT /I,000 YDS   37~I7 M /I,000 M | 19.7~21.3 FT   6~6.5 M | 19~20 MM   | 63.8 OZ   1810 G |
| 3   | ENDEAVOR HD 65A        | 15~45 X 65 | 144~68 FT /1,000 YDS   48~23 M /1,000 M | 14.8~18 FT   4.5~5.5 M | 19~20 MM   | 51.1 OZ   1450 G |
| =   | ENDEAVOR XF 80A        | 20~60 X 80 | IIO~52 FT /I,000 YDS   37~17 M /I,000 M | 19.7~21.3 FT   6~6.5 M | 19~20 MM   | 59.3 OZ   1680 G |
| S   | <b>ENDEAVOR XF</b> 60A | 15~45 X 60 | 141~68 FT /1,000 YDS   47~23 M /1,000 M | 16.4~19.7 FT   5~6 M   | 19~20 MM   | 45.I OZ   I280 G |
|     | VEO HD 80A             | 20~60 X 80 | IIO~52 FT /I,000 YDS   37~I7 M /I,000 M | 19.7~21.3 FT   6~6.5 M | 19~20 MM   | 54.7 OZ   1550 G |
| PES | VEO HD 60A             | 15~45 X 60 | 141~68 FT /1,000 YDS   47~23 M /1,000 M | 16.4~19.7 FT   5~6 M   | 19~20 MM   | 42.5 OZ   1205 G |
| SS  | VESTA 560A             | 15-45 X 60 | 104~63 FT /I,000 YDS   35~21 M /I,000 M | 26.3~29.5 FT   8~9 M   | 16~21 MM   | 45.7 OZ   1293 G |
|     | VESTA 460A             | 15-50 X 60 | 125~57 FT /I,000 YDS   42~19 M /I,000 M | 32.8~39.4 FT   10~12 M | II MM      | 21.5 OZ  609 G   |
|     | VESTA 350A             | 12-45X 50  | 157~52 FT /I,000 YDS   52~17 M /I,000 M | 19.7~21.3 FT   6~6.5 M | II MM      | 21.2 OZ  600 G   |

|            |                            | SIZE    | FIELD OF VIEW                      | NEAR FOCUS      | EYE RELIEF | ADJUST. PUPILLARY | WEIGHT          |
|------------|----------------------------|---------|------------------------------------|-----------------|------------|-------------------|-----------------|
| B          | ENDEAVOR ED IV 1042        | 10 X 42 | 340 FT /I,000 YDS   II4 M /I,000 M | 5.9 FT   I.8 M  | 19 MM      | 56~74 MM          | 27.7 OZ   786 G |
| BINOCULARS | <b>ENDEAVOR ED IV</b> 8420 | 8 X 42  | 377 FT /I,000 YDS   I26 M /I,000 M | 5.9 FT   I.8 M  | 19 MM      | 56~74 MM          | 27.7 OZ   786 G |
| Ë          | ENDEAVOR ED II 1042        | 10 X 42 | 340 FT /I,000 YDS   II4 M /I,000 M | 6.6 FT   2 M    | 18 MM      | 56~74 MM          | 27.2 OZ   770 G |
| AR         | <b>ENDEAVOR ED II 8420</b> | 8 X 42  | 377 FT /I,000 YDS   I26 M /I,000 M | 6.6 FT   2 M    | 19.5 MM    | 56~74 MM          | 27.2 OZ   770 G |
| 85 C       | ENDEAVOR ED 1042           | 10 X 42 | 340 FT /I,000 YDS   II4 M /I,000 M | 8.2 FT   2.5 M  | 16.5 MM    | 58~74 MM          | 25.8 OZ   730 G |
|            | ENDEAVOR ED 8420           | 8 X 42  | 367 FT /I,000 YDS   I22 M /I,000 M | 6.6 FT   2 M    | 19 MM      | 58~74 MM          | 25.8 OZ   730 G |
| 2          | ENDEAVOR ED 8320           | 8 X 32  | 377 FT /I,000 YDS   I26 M /I,000 M | 6.6 FT   2 M    | 17.5 MM    | 55~74 MM          | 19.1 OZ   540 G |
| 8          | <b>VEO HD IV</b> 1042      | 10 X 42 | 340 FT /I,000 YDS   II4 M /I,000 M | 5.9 FT   I.8 M  | 19 MM      | 56~74 MM          | 27.7 OZ   786 G |
| MONOCULARS | <b>VEO HD IV</b> 8420      | 8 X 42  | 377 FT /I,000 YDS   I26 M /I,000 M | 5.9 FT   I.8 M  | 19 MM      | 56~74 MM          | 27.7 OZ   786 G |
| R          | VEO HD 2 1042              | 10 X 42 | 340 FT /I,000 YDS   II4 M /I,000 M | 6.5 FT   2 M    | 18 MM      | 58~74 MM          | 25.4 OZ   720 G |
|            | VEO HD 2 8420              | 8 X 42  | 374 FT /I,000 YDS   I24 M /I,000 M | 6.5 FT   2 M    | 19 MM      | 55~74 MM          | 25.4 OZ   720 G |
| SPEC       | VEO HD 2 1042M             | 10 X 42 | 342 FT /I,000 YDS   II4 M /I,000 M | 6.5 FT   2 M    | 18 MM      | -                 | II.5 OZ   325 G |
|            | VEO HD 1042                | 10 X 42 | 342 FT /I,000 YDS   II4 M /I,000 M | 6.6 FT   2 M    | 18 MM      | 58~74 MM          | 27.1 OZ   767 G |
|            | VEO HD 8420                | 8 X 42  | 372 FT /I,000 YDS   I24 M /I,000 M | 6.6 FT   2 M    | 19 MM      | 58~74 MM          | 26.8 OZ   760 G |
|            | <b>VEO ED</b> 1250         | 12 X 50 | 25I FT /I,000 YDS   84 M /I,000 M  | II.5 FT   3.5 M | 18 MM      | 60~75 MM          | 26.8 OZ   760 G |
|            | <b>VEO ED</b> 1050         | 10 X 50 | 282 FT /I,000 YDS   94 M /I,000 M  | 9.8 FT   3 M    | 19 MM      | 59.5~75 MM        | 27.6 OZ   782 G |
|            | <b>VEO ED</b> 1042         | 10 X 42 | 314 FT /1,000 YDS   105 M /1,000 M | 9.2 FT   2.8 M  | 16 MM      | 55~75 MM          | 22.6 OZ   640 G |
|            | <b>VEO ED</b> 8420         | 8 X 42  | 330 FT /I,000 YDS   IIO M /I,000 M | 8.2 FT   2.5 M  | 19 MM      | 55~75 MM          | 22.6 OZ   640 G |
|            | <b>VEO ED</b> 8420M        | 8 X 42  | 324 FT /I,000 YDS   I08 M /I,000 M | 8.2 FT   2.5 M  | 19 MM      | -                 | 10.6 OZ   300 G |
| HEY        | VEO XF 1042                | 10 X 42 | 332 FT /I,000 YDS   III M /I,000 M | 6.9 FT   2.1 M  | 16 MM      | 57~74 MM          | -               |
| HEN        | VEO XF 8420                | 8 X 42  | 409 FT /I,000 YDS   I36 M /I,000 M | 6.9 FT   2.1 M  | 20 MM      | 57~74 MM          | -               |
|            | VESTA 1042                 | 10 X 42 | 298 FT /I,000 YDS   I00 M /I,000 M | 6.9 FT   2.1 M  | 17 MM      | 56~74 MM          | 20.8 OZ   590 G |
|            | VESTA 1025                 | 10 X 25 | 330 FT /I,000 YDS   IIO M /I,000 M | 8.2 FT  2.5 M   | IO MM      | 56~74 MM          | 9.88 OZ   280 G |
|            | VESTA 8420                 | 8 X 42  | 325 FT /I,000 YDS   108 M /I,000 M | 6.9 FT   2.1 M  | 19 MM      | 56~74 MM          | 21.5 OZ   610 G |
|            | VESTA 8250                 | 8 X 25  | 340 FT /I,000 YDS   II4 M /I,000 M | 8.2 FT   2.5 M  | 12.5 MM    | 56~74 MM          | 9.88 OZ   280 G |
|            | VESTA 8320M                | 8 X 32  | 392 FT /I,000 YDS   131 M /I,000 M | 6.6 FT   2 M    | 17.7 MM    | -                 | 8.8 OZ   250 G  |

|                   | LEG<br>MATERIAL   | FOLDED HEIGH<br>[IN/MM]  | EXTENDED HT.<br>[IN/MM]  | STANDARD HT.<br>[IN/MM]  | LEG DIAM.<br>[ MM ]  | LEG SECT.   | HEAD   | QUICK<br>SHOE  | MAX LOAD<br>[LBS/KG]  | WEIGHT<br>[LBS/G]  |
|-------------------|---|--|--|--|--|---|--|--|---|--|
| VEO 3 303AV20     | ALUMINUM  | 28.4 / 722   | 71.3 / 1810  | 57.9 / 1472  | 30   | 3   | VEO PV-20  | QS-67  | 13.2 / 6  | 7.1 / 3241   |
| VEO 3 303CV20     | CARBON FIBER  | 28.4 / 722   | 71.3 / 1810  | 57.9 / 1472  | 30   | 3   | VEO PV-20  | QS-67  | 13.2 / 6  | 6.4 / 2894   |
| VEO 3 303AVI8     | ALUMINUM  | 28.4 / 722   | 71.3 / 1810  | 57.9 / 1472  |  | 3   | VEO PV-18  | QS-67  |   | 6.4 / 2894   |
| VEO 3 303CV18     | CARBON FIBER  | 28.4 / 722   |  | 57.9 / 1472  |  |   | VEO PV-18  |  |   | 6.4 / 2894   |
| VEO 3 263AVI6     | ALUMINUM  | 28.4 / 722   |  | 57.9 / 1472  |  |   | VEO PV-16  |  |   | 6.4 / 2894   |
| VEO 3 264AVI6     | ALUMINUM  | 28.4 / 722   |  | 57.9 / 1472  |  |   | VEO PV-20  | QS-67  |   | 6.4 / 2894   |
| VEO 3 264AVI6 LVL | ALUMINUM  | 28.4 / 722   | 71.3 / 1810  | 57.9 / 1472  | 30   | 3   | VEO PV-20  | QS-67  | 13.2 / 6  | 6.4 / 2894   |
|                   | VEO 3 303CV20  VEO 3 303AVI8  VEO 3 303CVI8  VEO 3 263AVI6  VEO 3 264AVI6 | MATERIAL  VEO 3 303AV20 ALUMINUM  VEO 3 303CV20 CARBON FIBER  VEO 3 303CV18 ALUMINUM  VEO 3 263AV16 ALUMINUM  VEO 3 264AV16 ALUMINUM | MATERIAL         [ IN / MM ]           VEO 3 303AV20         ALUMINUM         28.4 / 722           VEO 3 303CV20         CARBON FIBER         28.4 / 722           VEO 3 303AVIB         ALUMINUM         28.4 / 722           VEO 3 303CVIB         CARBON FIBER         28.4 / 722           VEO 3 263AVI6         ALUMINUM         28.4 / 722           VEO 3 264AVI6         ALUMINUM         28.4 / 722 | MATERIAL         [ IN/MM]         [ IN/MM]           VEO 3 303AV20         ALUMINUM         28.4 / 722         71.3 / 1810           VEO 3 303CV20         CARBON FIBER         28.4 / 722         71.3 / 1810           VEO 3 303AV18         ALUMINUM         28.4 / 722         71.3 / 1810           VEO 3 303CV18         CARBON FIBER         28.4 / 722         71.3 / 1810           VEO 3 263AV16         ALUMINUM         28.4 / 722         71.3 / 1810           VEO 3 264AV16         ALUMINUM         28.4 / 722         71.3 / 1810 | MATERIAL         [ IN / MM ]         [ IN / MM ]         [ IN / MM ]           VEO 3 303AV20         ALUMINUM         28.4 / 722         71.3 / 1810         57.9 / 1472           VEO 3 303CV20         CARBON FIBER         28.4 / 722         71.3 / 1810         57.9 / 1472           VEO 3 303AV18         ALUMINUM         28.4 / 722         71.3 / 1810         57.9 / 1472           VEO 3 303CV18         CARBON FIBER         28.4 / 722         71.3 / 1810         57.9 / 1472           VEO 3 263AV16         ALUMINUM         28.4 / 722         71.3 / 1810         57.9 / 1472           VEO 3 264AV16         ALUMINUM         28.4 / 722         71.3 / 1810         57.9 / 1472 | MATERIAL         [ IN / MM ]         [ IN / MI]         [ IN / MI] | MATERIAL         [ IN / MM ]         LEG SECT.           VEO 3 303AV20         ALUMINUM         28.4 / 722         71.3 / 1810         57.9 / 1472         30         3           VEO 3 303CV20         CARBON FIBER         28.4 / 722         71.3 / 1810         57.9 / 1472         30         3           VEO 3 303AV18         ALUMINUM         28.4 / 722         71.3 / 1810         57.9 / 1472         30         3           VEO 3 303CV18         CARBON FIBER         28.4 / 722         71.3 / 1810         57.9 / 1472         30         3           VEO 3 263AV16         ALUMINUM         28.4 / 722         71.3 / 1810         57.9 / 1472         30         3           VEO 3 264AV16         ALUMINUM         28.4 / 722         71.3 / 1810         57.9 / 1472         30         3 | MATERIAL         [IN/MM]         [IN/MM]         [IN/MM]         [MM]         LEG SECT.         HEAD           VEO 3 303AV20         ALUMINUM         28.4/722         71.3/1810         57.9/1472         30         3         VEO PV-20           VEO 3 303CV20         CARBON FIBER         28.4/722         71.3/1810         57.9/1472         30         3         VEO PV-20           VEO 3 303AV18         ALUMINUM         28.4/722         71.3/1810         57.9/1472         30         3         VEO PV-18           VEO 3 303CV18         CARBON FIBER         28.4/722         71.3/1810         57.9/1472         30         3         VEO PV-18           VEO 3 263AV16         ALUMINUM         28.4/722         71.3/1810         57.9/1472         30         3         VEO PV-16           VEO 3 264AV16         ALUMINUM         28.4/722         71.3/1810         57.9/1472         30         3         VEO PV-20 | MATERIAL         [IN/MM]         [IN/MM]         [MM]         LEG SECT.         HEAD         SH0E           VEO 3 303AV20         ALUMINUM         28.4/722         71.3/1810         57.9/1472         30         3         VEO PV-20         QS-67           VEO 3 303CV20         CARBON FIBER         28.4/722         71.3/1810         57.9/1472         30         3         VEO PV-20         QS-67           VEO 3 303AV18         ALUMINUM         28.4/722         71.3/1810         57.9/1472         30         3         VEO PV-18         QS-67           VEO 3 303CV18         CARBON FIBER         28.4/722         71.3/1810         57.9/1472         30         3         VEO PV-18         QS-67           VEO 3 263AV16         ALUMINUM         28.4/722         71.3/1810         57.9/1472         30         3         VEO PV-16         QS-67           VEO 3 264AV16         ALUMINUM         28.4/722         71.3/1810         57.9/1472         30         3         VEO PV-20         QS-67 | MATERIAL         [IN/MM]         [IN/MM]         [MM]         LEG SECT.         HEAD         SHOE         [LBS/KG]           VEO 3 303AV20         ALUMINUM         28.4/722         71.3/1810         57.9/1472         30         3         VEO PV-20         QS-67         13.2/6           VEO 3 303CV20         CARBON FIBER         28.4/722         71.3/1810         57.9/1472         30         3         VEO PV-20         QS-67         13.2/6           VEO 3 303AV18         ALUMINUM         28.4/722         71.3/1810         57.9/1472         30         3         VEO PV-18         QS-67         13.2/6           VEO 3 303CV18         CARBON FIBER         28.4/722         71.3/1810         57.9/1472         30         3         VEO PV-18         QS-67         13.2/6           VEO 3 263AV16         ALUMINUM         28.4/722         71.3/1810         57.9/1472         30         3         VEO PV-16         QS-67         13.2/6           VEO 3 264AV16         ALUMINUM         28.4/722         71.3/1810         57.9/1472         30         3         VEO PV-20         QS-67         13.2/6 |

|                 | LEG<br>MATERIAL | FOLDED HEIGH<br>[IN/MM] | EXTENDED HT.<br>[IN/MM] | STANDARD HT.<br>[IN/MM] | LEG DIAM.<br>[MM] | LEG SECT. | HEAD        | QUICK<br>SHOE | MAX LOAD<br>[LBS / KG] | WEIGHT<br>[LBS/G] |
|-----------------|-----------------|-------------------------|-------------------------|-------------------------|-------------------|-----------|-------------|---------------|------------------------|-------------------|
| ₹ VEO 3 263CVI6 | CARBON FIBER    | 28.4 / 722              | 71.3 / 1810             | 57.9 / 1472             | 30                | 3         | VEO PV-20   | QS-67         | 13.2 / 6               | 6.4 / 2894        |
| ✓ VEO 3 264CVI6 | CARBON FIBER    | 28.4 / 722              |                         | 57.9 / 1472             |                   |           | VEO PV-20   |               |                        | 6.4 / 2894        |
| VEO 3 264AVI5   | ALUMINUM        | 22.6 / 575              | 61.2 / 1555             | 48.3 / 1227             | 26                | 4         | VEO PV-15   | QS-6IP        | 11/5                   | 5.3 / 2400        |
| YEO 3 264CVI5   | CARBON FIBER    | 22.6 / 575              | 61.2 / 1555             | 48.3 / 1227             | 26                | 4         | VEO PV-15   | QS-6IP        | 11/5                   | 4.8 /2200         |
| ₩ VEO 3 303AB   | ALUMINUM        | 29.3 / 745              | 72.1 / 1831             | 58.8 / 1495             | 30                | 3         | VEO BH-250S | QS-62V3       | 55.1 / 25              | 5.7 / 2585        |
| VEO 3 304AB     | ALUMINUM        | 26.2/665                | 71.9 / 1826             | 58.8 / 1494             | 30                | 4         | VEO BH-250S | QS-62V3       | 55.1 / 25              | 5.7 / 2586        |
| VEO 3 263AB     | ALUMINUM        | 29.1 / 738              | 70.7 / 1795             | 57.7 / 1465             | 26                | 3         | VEO BH-160S | QS-62V3       | 33.1 / 15              | 4.7 / 2142        |
| VEO 3 303CB     | CARBON FIBER    | 29.3 / 745              | 72.1 / 1831             | 58.8 / 1495             | 30                | 3         | VEO BH-250S | QS-62V3       | 55.1 / 25              | 4.9 / 2238        |
| VEO 3 304CB     | CARBON FIBER    | 26.2/665                | 71.9 / 1826             | 58.8 / 1494             | 30                | 4         | VEO BH-250S | QS-62V3       | 55.1 / 25              | 4.98 / 2259       |
| VEO 3 263CB     | CARBON FIBER    | 29.1 / 738              | 70.7 / 1795             | 57.7 / 1465             | 26                | 3         | VEO BH-160S | QS-62V3       | 33.1 / 15              | 4.2 / 1900        |
| VEO 3 263AO     | ALUMINUM        | 27.9 / 708              | 69.4 / 1763             | 56.4 /1432              | 26                | 3         | VEO PH-28   | QS-6IP        | 17.6 / 8               | 5.2 / 2360        |
| VEO 3 264AO     | ALUMINUM        | 22.6 / 575              | 61.2 / 1555             | 48.3 / 1227             | 26                | 4         | VEO PH-28   | QS-6IP        | 17.6 / 8               | 5.1 / 2320        |
| VEO 3 233AO     | ALUMINUM        | 25 / 636                | 61.2 / 1555             | 49.2 / 1250             | 23                | 3         | VEO PH-26   | QS-7IP        | 13.2 / 6               | 4.1 / 1860        |
| VEO 3 263CO     | CARBON FIBER    | 27.9 / 708              | 69.4 / 1763             | 56.4 /1432              | 26                | 3         | VEO PH-28   | QS-6IP        | 17.6 / 8               | 4.6 / 2100        |
| VEO 3 264CO     | CARBON FIBER    | 22.6 / 575              | 22.6 / 575              | 48.3 / 1227             | 26                | 4         | VEO PH-28   | QS-6IP        | 17.6 / 8               | 4.7 / 2120        |
| ₹ VEO 3 233CO   | CARBON FIBER    | 25 / 636                | 61.2 / 1555             | 49.2 / 1250             | 23                | 3         | VEO PH-26   | QS-7IP        | 13.2 / 6               | 3.7 / 1680        |
| VEO 3T 265HABP  | ALUMINUM        | 17.3 / 439              | 65.4 / 1660             | 50.2 / 1275             | 26                | 5         | VEO BP-I20T | QS-72T        | 26.4 / 12              | 4.7 / 2115        |
| VEO 3T 235ABP   | ALUMINUM        | 16.1 / 410              | 61.0 / 1550             | 45.5 / 1155             | 23                | 5         | VEO BP-50T  | QS-72T        | 17.6 / 8               | 3.8 / 1745        |
| VEO 3T 204ABP   | ALUMINUM        | 15.9 / 405              | 55.1 /1400              | 40.9 / 1040             | 20                | 4         | VEO BP-45T  | QS-72T        | 8.8 / 4                | 3.3 / 1490        |
| VEO 3TT 233ABP  | ALUMINUM        | 9.7 / 245               | 22.1 / 560              | 19.1 / 486              | 23                | 3         | VEO BP-50T  | QS-72T        | 17.6 / 8               | 2.6 / 1161        |
| VEO 3TT 203ABP  | ALUMINUM        | 9.1 / 225               | 19.7 /500               | 57.7 / 443              | 20                | 3         | VEO BP-45T  | QS-72T        | 8.8 / 4                | 2.2 / 977         |
| VEO 3T 265HCBP  | CARBON FIBER    | 17.3 / 439              | 65.4   1660             | 50.2 / 1275             | 26                | 5         | VEO BP-I20T | QS-72T        | 26.4 / 12              | 4.2 / 1910        |
| VEO 3T 235CBP   | CARBON FIBER    | 16.1 / 410              | 61.0 / 1550             | 45.5 / 1155             | 23                | 5         | VEO BP-50T  | QS-72T        | 17.6 / 8               | 3.5 / 1600        |
| VEO 3T 204CBP   | CARBON FIBER    | 15.9 / 405              | 55.1 /1400              | 40.9 / 1040             | 20                | 4         | VEO BP-45T  | QS-72T        | 8.8 / 4                | 3.0 / 1375        |
| VEO 3TT 233CBP  | CARBON FIBER    | 9.7 / 245               | 22.1 / 560              | 19.1 / 486              | 23                | 3         | VEO BP-50T  | QS-72T        | 17.6 / 8               | 2.4 / 1101        |
| VEO 3T 235AP    | ALUMINUM        | 16.1 / 410              | 60.4 /1535              | 44.9 / 1140             | 23                | 5         | VEO PH-20   | QS-65         | 13.2 / 6               | 3.6 / 1648        |
| VEO 3TT 233AP   | ALUMINUM        | 9.7 / 245               | 21.2 / 538              | 18.4 / 446              | 23                | 3         | VEO PH-20   | QS-65         | 13.2 / 6               | 2.4 / 1100        |
| VEO 3T 235CP    | CARBON FIBER    | 16.1 / 410              | 60.4 /1535              | 44.9 / 1140             | 23                | 5         | VEO PH-20   | QS-65         | 13.2 / 6               | 3.3 / 1498        |
| VEO 3GO 265HAB  | ALUMINUM        | 16.1 / 410              | 65.5 / 1665             | 49.6 / 1260             | 26                | 5         | ALTA BH-102 | QS-60 V2      | 22 / 10                | 3.6 / 1659        |
| VEO 3GO 235AB   | ALUMINUM        | 12.9 / 330              | 53.5 / 1360             | 41.7 / 1060             | 23                | 5         | T-50        | QS-65         | 11/5                   | 2.7 / 1225        |
| VEO 3GO 204AB   | CARBON FIBER    | 13.6 / 345              | 51.5 / 1310             | 39.8 / 1010             | 20                | 4         | T-45        | QS-65         | 6.6/3                  | 2.1 / 945         |
| VEO 3GO 265HCB  | CARBON FIBER    | 65.5 / 1665             | 65.5 / 1665             | 49.6 / 1260             | 26                | 5         | ALTA BH-102 | QS-60 V2      | 22 / 10                | 3.1 / 1415        |
| VEO 3GO 235CB   | CARBON FIBER    | 12.9 / 330              | 53.5 / 1360             | 41.7 / 1060             | 23                | 5         | T-50        | QS-65         | 11/5                   | 2.3 / 1065        |
| VEO 3GO 204CB   | CARBON FIBER    | 13.6 / 345              | 51.6 / 1310             | 39.8 / 1010             | 20                | 4         | T-45        | QS-65         | 6.6 / 3                | 1.8 / 816         |
| √ VEO 3GO 235AP | ALUMINUM        | 13.4 / 340              | 53.4 /1335              | 41.6 / 1058             | 23                | 5         | VEO 2 PH-25 | QS-65         | 7.7 / 3.5              | 2.7 / 1239        |
| VEO 3GOT 233AP  | ALUMINUM        | 13.4 / 340              | 53.4 /1335              | 41.6 / 1058             | 23                | 5         | VEO 2 PH-25 | QS-65         | 7.7 / 3.5              | 2.7 / 1239        |

|    |                 | LEG<br>Material | FOLDED HEIGH<br>[IN/MM] | EXTENDED HT.<br>[IN/MM] | STANDARD HT.<br>[IN/MM] | LEG DIAM.<br>[MM] | LEG SECT. | HEAD           | QUICK<br>SHOE | MAX LOAD<br>[LBS / KG] | WEIGHT<br>[LBS/G] |
|----|-----------------|-----------------|-------------------------|-------------------------|-------------------------|-------------------|-----------|----------------|---------------|------------------------|-------------------|
| 균  | VEO 3GOT 203AP  | ALUMINUM        | 13.4 / 340              | 53.4 /1335              | 41.6 / 1058             | 23                | 5         | VEO 2 PH-25    | VEO 2 PH-25   | 7.7 / 3.5              | 2.7 / 1239        |
| PO | VEO 3GO 235CP   | CARBON FIBER    | 13.4 / 340              | 53.4 /1335              | 41.6 / 1058             | 23                | 5         | VEO 2 PH-25    | QS-65         | 7.7 / 3.5              | 24/1080           |
| DS | VEO 3GO 204CP   | CARBON FIBER    | 14.2 / 360              | 52.6 /1335              | 40.1 / 1018             | 20                | 4         | VEO 2 PH-25    | QS-65         | 7.7 / 3.5              | 2.1 / 947         |
| Sp | VEO 2PRO 263AO  | ALUMINUM        | 24 / 610                | 63 / 1600               | 50.8 / 1290             | 26                | 3         | VEO 2 PH-28    | QS-6IP        | 11/5                   | 4.24 / 1926       |
| EC | VEO 2PRO 233AO  | ALUMINUM        | 22 / 560                | 57.5 / 1460             | 45.7 / 1160             | 23                | 3         | VEO 2 PH-28    | QS-6IP        | 8.8 / 4                | 3.71 / 1683       |
|    | VEO 2PRO 203AO  | ALUMINUM        | 22 / 560                | 57.5 / 1460             | 45.9 / 1165             | 20                | 3         | VEO 2 PH-26    | QS-60 V2      | 6.6 / 3                | 3.14 / 1425       |
|    | VESTA TB 235AB  | ALUMINUM        | 14.8 / 375              | 56.3 / 1430             | 48.6 /1235              | 23                | 5         | T-51           | QS-65         | 9.9 / 4.5              | 2.65 / 1200       |
|    | VESTA TB 204AB  | ALUMINUM        | 14.8 / 375              | 51.1 / 1300             | 41.5 / 1055             | 20                | 4         | T-46           | QS-65         | 6.6 / 3                | 2.06 / 934        |
|    | VESTA TB 204ABS | ALUMINUM        | 12.4 / 315              | 39.7 / 1010             | 35.4 / 900              | 20                | 4         | T-46           | QS-65         | 6.6 / 3                | 1.82 / 825        |
|    | VESTA TB 235CB  | CARBON FIBER    | 14.8 / 375              | 56.3 / 1430             | 48.6 / 1235             | 23                | 5         | T-51           | QS-65         | 9.9 / 4.5              | 2.27 / 1031       |
|    | VESTA TB 204CB  | CARBON FIBER    | 14.8 / 375              | 51.1 / 1300             | 41.5 / 1055             | 20                | 4         | T-46           | QS-65         | 6.6 / 3                | 1.77 / 802        |
|    | VESTA 233AP     | ALUMINUM        | 22.9 / 582              | 61 / 1550               | 48.1 /1221              | 23                | 3         | PH-23          | QS-29         | 7.7 / 3.5              | 2.8 / 1275        |
|    | VESTA 203AP     | CARBON FIBER    | 22.4 / 570              | 61 / 1550               | 48 / 1220               | 20                | 3         | PH-23          | QS-29         | 7.7 / 3.5              | 2.4 / 1105        |
|    | VESTA 203AGH    | CARBON FIBER    | 22.4 / 570              | 61 / 1550               | 48.2 / 1255             | 20                | 3         | GH-45          | QS-29         | 7.7 / 3.5              | 2.5 / 1120        |
|    | VESTA 204AP     | ALUMINUM        | 20.5 / 520              | 61 / 1550               | 49.4 / 1255             | 20                | 4         | PH-23          | QS-29         | 7.7 / 3.5              | 2.5 / 1132        |
|    | ESPOD CX I      | ALUMINUM        | II.6 / 295              | 21.3 / 540              | -                       | -                 | 3         | -              | -             | 5.5 / 2.5              | 147 /665          |
|    | ESPOD CX I OS   | ALUMINUM        | 14.8 / 375              | 24.4 / 620              | -                       | -                 | 3         | 3 WAY PAN HEAD | QS-14         | 6.6 / 3                | 2.1 / 934         |
|    | VESTA TTI       | ALUMINUM        | 6.89 / 175              | 3.94 / 100              | -                       | -                 | -         | BALL HEAD      | -             | 44/2                   | 0.34 /156         |
|    | VS-82           | ALUMINUM        | 10 / 255                | 9.25 / 235              | -                       | -                 | -         | -              | -             | 5.5 / 2.5              | 0.94 / 430        |

|              |                        | FOLDED HEIGH<br>[IN/MM] | EXTENDED HT.<br>[IN/MM] | LEG DIAM.<br>[MM] | WEIGHT<br>[LBS/G] |
|--------------|------------------------|-------------------------|-------------------------|-------------------|-------------------|
|              | ENDEAVOR 303AGM        | 13.4 / 340              | 53.4 /1335              | 23                | 2.7 / 1239        |
|              | ENDEAVOR 303CGM        | 13.4 / 340              | 53.4 /1335              | 23                | 2.4 / 1080        |
|              | <b>EQUALIZER</b> IQS   | 6.9 / 176               | 10 / 255                | 14                | 0.7 / 320         |
|              | <b>EQUALIZER</b> 20S   | II / 277                | 28 / 715                | 17                | 1 / 453           |
| SUP          | EQUALIZER 2            | 12.7 / 325              | 27 / 685                | 17                | 0.9 / 430         |
| <u> </u>     | <b>VEO 2 AM-234TU</b>  | 24.4 / 620              | 62.6 / 1590             | 23                | 1.95 / 885        |
| 끅            | <b>VEO 2 CM-</b> 234TU | 24.4 / 620              | 62.6 / 1590             | 23                | 1.78 / 809        |
| <del>S</del> | <b>QUEST</b> T62U      | 27.5 / 700              | 62 / 1575               | 20                | 2.2 / 1000        |
| 3            | QUEST M49              | 22 / 560                | 49 / 1245               | 20                | 0.66 / 300        |
|              | QUEST M62              | 26.3 / 670              | 62 / 1575               | 20                | 0.77 / 350        |
|              | <b>QUEST</b> B38       | 19.1 / 485              | 38 / 965                | 20                | 1.14 / 520        |
|              | QUEST B62              | 27.1 / 690              | 62 / 1575               | 20                | 1.43 / 650        |
|              | SCOUT M62              | 22 / 560                | 62 / 1575               | 20                | 0.57 / 260        |
|              | SCOUT B62              | 22.2 / 565              | 49 / 1245               | 20                | 1.1 / 500         |

|          |                      | LATERAL TILT [°] | FRONTAL TILT [°] | ROTATION<br>[°] | QUICK<br>SHOE | MAX LOAD<br>[LBS / KG] | WEIGHT<br>[LBS/G] |
|----------|----------------------|------------------|------------------|-----------------|---------------|------------------------|-------------------|
| HEADS SP | VEO PH-28            | -                | ~60° ~90°        | 360             | QS-6IP        | 17.6 / 8               | 14 / 639.5        |
|          | VEO PH-26            | -                | -                | 360             | QS-6IP        | 13.2 / 6               | 1.1 / 510         |
|          | <b>VEO PV-20</b>     | -                | ~60° ~90°        | 360             | QS-67         | 13.2 / 6               | 2.2 / 1096        |
| ğ        | VEO PV-18            |                  |                  |                 | 1 / 453       | 1 / 453                | 1.5 / 711         |
|          | VEO2 PH-28WM         | -                | 60° TO +90°      | 360             | QS-6IP        | 8.8 / 4                | 1.4 / 675         |
|          | <b>VEO2 BH-</b> 50WM | -91° TO +40°     | -                | 3621            | QS-6IP        | 11/5                   | 11/5              |
|          | PH-304               | +90° TO -60°     | 0° TO +90°       | 3621            | -             | 8.8 / 4                | 1.6 / 730         |
|          | ENDEAVOR GM-70       |                  |                  |                 |               |                        |                   |